


## 4 channel programmer weekly cycle with programming key

### EG403E


#### Presentation

- Product delivered with current time and date set.
- Automatic change of summer/winter time.
- Programming key
  - For permanent overrides
  - For program copy or save
- 300 programme steps ; ON, OFF, pulses  $\square$  or  $\square\square$ .
- Permanent overrides On or Off (☺ permanent light on).
- Temporary overrides On or Off (☺ flashing).
- Overrides (temporary, permanent or time delayed) remote activation possible.
- Simulation of presence ☺.
- Keyboard lock function by PIN number.
- Counter of operating time on every output.
- Programmable with power off.
- Display with backlight.

#### Product Presentation



#### Connection diagram



## User instructions

### Technical specifications

#### Electrical characteristics

- Supply voltage 230 V +10/-15%
- Frequency 50/60 Hz
- Power consumption < 2 VA
- Output 2 changeover + 2 NO contacts
- Maximum load
  - AC1  $\mu$  10A 250 V~
  - Incandescent lighting: 1500 W
  - Halogen lighting
  - Compensated fluorescent tubes // (max. 45  $\mu$ F) 400 W
  - Non compensated fluorescent tubes, compensated in series 1000 W
  - Compact fluorescent lamps 400 W
- Minimum load
  - AC1 100 mA 250 V~
- Galvanic insulation between power supply and output < 4 kV
- Rated impulse voltage 4 kV

#### Functional characteristics

- Programming capacity 300 steps
- Minimum time between 2 steps 1 minute
- Running accuracy  $\pm 0,2$  sec/ 24h
- Operating reserve lithium battery, total of 5 years autonomy (unlimited programme backup)
- The product is set into standby state (display switched-off) after 1 minute with power off. It switches back into automatic mode as soon as power is back on or when pressing any key.
- Protection degree IP 20 / IK 04
- Action type 1B
- Degree of pollution 2
- Software class A

#### Environment

- Operating temperature -10 °C to +50 °C
- Storage temperature -20 °C to +70 °C
- Temperature for the ball pressure Test 75° to 125°C

#### Connection by quick-connect terminals

- Flexible 0,75 to 2,5 mm<sup>2</sup>
- Rigid 0,75 to 2,5 mm<sup>2</sup>

#### Standards

60730-1  
60730-2-7

Usable in all Europe and in Switzerland



This device must be installed only by a qualified electrician according to the installation standards in force in the country.

#### Warranty NOT APPLICABLE FOR AUSTRALIA

A warranty period of 24 months is offered on hager products, from date of manufacture, relating to any material of manufacturing defect. If any product is found to be defective it must be returned via the installer and supplier (wholesaler). The warranty is withdrawn if:

- after inspection by hager quality control dept the device is found to have been installed in a manner which is contrary to IEE wiring regulations and accepted practice within the industry at the time of installation.
- The procedure for the return of goods has not been followed. Explanation of defect must be included when returning goods.

## First commissioning

When using for the first time, the following settings must be done:

- select the language
- select the year, month, day
- select the hour and the minutes
- select the automatic change summer/winter.

Press the buttons +/- to set the display.  
Press OK to validate.

When the settings are finished, the clock goes to automatic mode.

## Reinitializing

Pressing simultaneously the menu, -, +, ok keys allows you to réinitialize the product.  
The program is kept in memory.


## Menu

Press the button menu to access the programming/setting mode.

All of the programming and adjustments are based on the following principle:


- the 1st line and/or 2nd line of the display indicate the requested setting,
- the buttons +/- allow navigation through the menus and settings,
- the button ok allows validation.

Pressing the button menu allows you to access the following settings:




At any time, pressing the button menu allows you to return to the previous choice level.

## PROGRAM prog



### PROGRAM CREATE

Creating the weekly programme:




\*The cycle programme is only possible if one or several cycles have been defined in the FUNCTION/CYCLE menu.


## Creating a holiday programme

The Holiday programme allows you to define one period during which the output contact is on ON or OFF.

This programme has the highest priority.



To define your Holiday programme:



Select:


- FIX DATE: if the programme must be repeated every year at the same dates.
- VARIABLE DATE ( ↔ ) if the dates must be recalculated every year according to the dates of Easter.
- NOT REPEATED: if the programme is to be activated once only.

Validate by ok.

### PROGRAMME READ

To visualise a programme

To check the steps of the recorded programme without risk of modifying or deleting.




The number of free program steps is displayed. Press ok to validate.

The buttons + and - allow you to scroll the programme steps.

At the end of the visualisation, press ok.

## PROGRAMME MODIFY

To modify one or several programme steps.




The number of free program steps is displayed. Press **ok** to validate. The buttons **+** and **-** allow you to scroll the programme steps. The button **ok** allows you to select the programme step to be modified.

## PROGRAMME DELETE

The menu delete allows you to erase:


- all of the programme contained in the clock.
- All of the programme on one channels.
- A programme step.



Everything deleted must be confirmed by pressing the button **ok**.

## PROGRAMME COPY


The copy function allows you to copy a programme from one channel to another.




Select the channel from which you wish to copy the programme. Select **(+, -)** then **ok** the program you wish to copy: WEEKLY, HOLIDAY. Select the channel into which you wish to paste the programme copied. Validate by pressing **ok**.

Select **CONTINUE**, if you wish to copy more programs. Select **BACK AUTO** to go back to the automatic mode.

## SETTINGS




The setting menu allows you to access the following settings:




### DATE-H

Time and day setting



Press **ok** to go back to automatic mode. For other settings (automatic changes summer/winter, language, reset), press **+** and select **CONTINUE**.

### SUMMER/WINTER



Select the type of summer/winter change required and then validate by **ok**.


Types available:

Type	Start of Summer time	Start of Winter time	Zone of application
EURO* SUMMER/WINTER	Last Sunday in March	Last Sunday in October	European Union
USA SUMMER/WINTER	Second Sunday of March	First Sunday in November	North America
AUSTRALIA SUMMER/WINTER	First Sunday in October	First Sunday in April	Australia
USER SUMMER/WINTER	Date freely programmed	Date freely programmed	
NO SUMMER/WINTER	No change	No change	

\* default type

When the **USER** type is chosen: Define the month, then the week of the change of summer time. Define the month, then the week of the change of winter time. The change always happens between 2 and 3 am. The change always happens on Sunday.

## LANGUAGE




Select the language required amongst the following : FRANÇAIS, DEUTSCH, **ENGLISH**, NEDERLANDS, PORTUGUES, ESPANOL, ITALIANA.

Validate by **ok**.

## FACTORY SETTINGS

Reset to zero

To reset the product to the manufacturer's configuration, that is to say, erase all of the programme as well as the settings made:




Confirm the complete reset by **ok**.


At the end of the reset to zero, as for the first commissioning, the following settings must be done:

- language
- selection of date and time
- Automatic summer/winter change.

## FUNCTIONS



The functions menu allows you to access the following functions and information:



## COUNTER


The "Counter" menu allows you to visualise the number operating hours (position ON) for every output, as well as the number of time changes since commissioning.

The counter also allows you to visualise the number of operating hours of the clock (product connected to mains supply).

The counters cannot be reset to zero (even after activating the function factory settings).

Press the button menu.

Using the buttons + or -, then ok, select the FUNCTIONS menu, then COUNTER.




The first line indicates the number of operating hours of the output.

The second line indicates the number of time changes (ON then OFF) done by the output.

The buttons + or - allow you to scroll the various indicators.

Press the button ok to exit this menu.




## CYCLE


In order to create a cycle programme you must have previously defined the operating cycle(s). A cycle is defined by x h, x min, x sec ON then x h, x min, x sec OFF.

This menu allows you to define, modify or deactivate up to 4 different cycles.


During the creation of a programme step, the active cycles appear in the choice of the state of output.



To create or modify a cycle:




To deactivate a cycle:



Deactivating a cycle also deactivates all the programme steps concerned.

## PIN-CODE



The menu PIN CODE allows you to lock the clock keyboard.


When the PIN number is active:

The symbol flashes to indicate that the function is activated.

After 1 minute without action on the product, the keyboard is locked.

The symbol indicates that the keyboard is locked. You must enter the PIN number to reactivate the keyboard.


To activate the keyboard lock by PIN code (or modify the PIN code)




With the buttons + or -, select ACTIVATE. Validate by ok.

With the buttons + or -, enter or modify the 4 figures of the PIN number. Validate by ok.

To deactivate the keyboard lock by PIN NUMBER



## INPUT




### Override input

This menu allows you to define:

- The product which operates the input (push button or switch).
- The function activated:
  - inversion of the state of output contact
  - time delay ON output activated for an adjustable time
  - Permanent OFF

- Permanent ON
- Random function
- The channel (or channels) concerned by the override input.



In automatic mode, the symbol indicates that an override coming from the override entry is active.

## Key

As soon as the key is present on the switch PROG KEY appears on the screen.

Two types of operation:

### A. Permanent override:

Insert the key into the switch.

After 10 seconds the program contained in the key will be executed without clearing the program contained in the time switch.

As soon as the key is removed the program of the time switch is again valid.

### B. Copy / Save:

The key allows you to save a program contained in the time switch. You can also copy the contents of the key to the clock.

1. Introduce the key PROG KEY appears on the screen. Press ok.

2. Using + or -, select:

**save on key:** to save the programme contained in the time switch.

**Record in clock:** to load the key programme into the time switch.

**apply key prog:** to execute the programme contained in the key without deleting the one present in the device.

**Key readout:** to check the programme contained in the key.

3. Validate your choice by ok.

An error message may appear on the screen: Check the type of key.

The error message remains on display as long as the key is present, but the time switch programme is the one which is executed

## Overrides

### Random operation

By successively pressing the channel command button.

If the output state is On :

1<sup>st</sup> press : temporary override. Off and flashing. Return to automatic mode will take place at the next programme step.

2<sup>nd</sup> press : permanent override. Off and are fixed. This override must be cancelled manually.

3<sup>rd</sup> press : forçage permanent. On and are fixed. This override must be cancelled manually.

4<sup>th</sup> press : Random operation. For the simulation of presence, as well as the state of output are displayed. Must be cancelled manually. In this case the programme steps are staggered at random in a slot of ± 59 min.

5<sup>th</sup> press : return to automatic mode. The state of output as well as the symbol are displayed.