



# **Product Environmental Profile**

# Push Button Cover for hw+ ACB range (PBC)



### **Company information**

#### Hager

132 Boulevard d'Europe F 67215 Obernai Cedex www.hagergroup.com

A question concerning the Product Environmental Profile: infopep@hager.com

### Methodology

PEP has been performed according to the PCR version PEP-PCR-ed4-2021 09 06 and PSR version No PSR issued by the PEP ecopassport program. For further information, please see the website of the program www.pep-ecopassport.org

### **References covered**

HWY089H, HWY089HSA, HWY090H, HWY090HSA

### **Reference product**

**Reference product identification** HWY089HSA

### **Functional unit**

This cover is an accessory used to lock out access to the circuit breaker opening (PUSH OFF) and closing (PUSH ON) push buttons. It prevents any unintentional or unauthorised operations. It consists of two transparent covers which can be locked with up to 3 padlocks:  $\emptyset$  6 mm (not supplied). The push buttons can be blocked independently or jointly.It can also keeps the opening push button pressed, thus preventing the circuit breaker from closing.

Use scenario based on : PSR product Category : No PSR 0

#### The functional unit is based on the use scenario recommended by the PCR for the category of the reference product.

### Materials and substances

All useful measures have been adopted to ensure that the materials used in the composition of the product do not contain any substances banned by the legislation in force at the time of marketing.

Plas	tics		Meta	ls		Oth	ers			
	g	%		g	%		g	%		
PC	9.33	21.2%	Steel	0.94	2.1%	Cardboard	22.12	50.4%		
PE-LD	0.47	1.1%	Silicon	0.06	0.1%	Paper	8.00	18.2%		
			Zinc	0.02	<0.1%	Wood	1.05	2.4%		
						Melamine cyanurate	1.04	2.4%		
						Paper	0.81	1.8%		
						Other	0.10	0.2%		
Total mass of reference product with raw material packaging : 43.93 g										
Total mass of reference product (Product + 41.822 g										

packaging)

### **System Boudaries**

The environmental information included in the PEP covers all the stages of the life cycle, from "cradle to grave".

Ма	nufactu	ring	Distribution	Installation		Use					End	of life		Module D		
Raw material extraction and processing	Transport to the manufacturer	Manufacturing	Distribution to the place of operation	Installation on the place of operation	Use or application of the product installed	Maintenance	Repair	Replacement	Restoration	Energy requirements during the use stage	Water requirements during the use stage	Deinstallation	Transport to the waste treatment site	Treatment of waste in view of its reuse, recovery and/or recycling	Disposal	Benefits and loads beyond the system boundaries
A1	A2	<b>A</b> 3	A4	A5	B1	<b>B2</b>	<b>B</b> 3	B4	B5	<b>B6</b>	B7	C1	C2	C3	C4	D
	Life cycle stages															

### Manufacturing

These products are manufactured by a site that has received an environmental certification ISO 14001.

This phase takes into account raw materials, manufacturing processes, production offcuts and their end-of-life treatment, upstream transport of materials and sub-assemblies to the manufacturing site, and transport from the manufacturing site to the final logistics platform.

### **Distribution**

The packaging has been designed in accordance with current regulations. In particular, the European directive 94/62/CE relative to packaging and packaging waste.

The used packaging is 100% recyclable or recoverable. Packaging and logistic flows are continuously improved in order to reduce their impact.

This phase taken into account the transport of the finished product, including packaging, to its place of use.

### Installation

#### Installation processes

The processes to install the product are not considered in this study because of their weak impact compared to the other life cycles steps.

This phase only take into account the impact of the the packaging waste treatment is taken into account.

#### Installation elements (non delivered with the product)

Elements non delivered with the product and needed to install the product are not considered.

### Use

For the considered scenario, the product has no energy consumption.

Energy model of the use phase : Europe

Consumables and maintenance : None

### End of life

Considering the complexity of the recycling channels for electric and electronic equipment impacts, we rely mainely on ESR modules (datasets for WEEE product end of life).

The recycling potential of the product is: 42%. The calculation of this rate is based on the method of the IEC/TR 62635.

### Environmental impacts

Evaluation of the environmental impact covers the following life cycle stages: raw materials + manufacturing (RMM), distribution (D), installation (I), use (U) and end of life (EoL).

All calculations are done with EIME software version 6.0.0 with the database version/Version CODDE® 2023-02 .

Indicators set : Indicators for PEF EF 3.0 (Compliance: PEP ed.4, EN15804+A2) v2.0

PEP representative of the covered products marketed in: Europe

Energy models considered for each phase

Manufacturing	Distribution	Installation	Use	End Of Life
A1-A3	A4	A5	B1-B7	C1-C4
China	-	Europe	Europe	Europe

#### Environmental impact indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Acidification (PEF-AP)	mole H+ eq	6.50E-04	4.50E-04	9.22E-05	0.00E+00	5.81E-05	1.25E-03	-1.07E-05
Climate change - Total (PEF-GWP)	kg CO2 eq.	1.42E-01	1.30E-02	3.54E-02	0.00E+00	2.81E-02	2.18E-01	-3.01E-03
Climate change-Biogenic (PEF-GWPb)	kg CO2 eq.	1.17E-02	0.00E+00	1.53E-03	0.00E+00	2.14E-04	1.35E-02	-3.23E-05
Climate change-Fossil (PEF-GWPf)	kg CO2 eq.	1.30E-01	1.30E-02	3.38E-02	0.00E+00	2.79E-02	2.05E-01	-2.98E-03
Climate change-Land use and land use change (PEF-GWPlu)	kg CO2 eq.	1.64E-05	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.64E-05	0.00E+00
Ecotoxicity, freshwater (PEF-CTUe)	CTUe	1.86E+00	7.93E-03	3.90E-01	0.00E+00	5.87E-02	2.31E+00	-6.88E-02
EF-particulate Matter (PEF-PM)	Incidence of diseases	3.75E-09	2.37E-09	5.52E-10	0.00E+00	4.31E-10	7.10E-09	-1.89E-10
Eutrophication, freshwater (PEF-Epf)	kg P eq.	8.76E-07	4.45E-09	4.58E-07	0.00E+00	2.52E-08	1.36E-06	-5.79E-07
Eutrophication marine (PEF-Epm)	kg N eq.	1.25E-04	1.06E-04	4.42E-05	0.00E+00	1.90E-05	2.95E-04	-1.83E-06
Eutrophication, terrestrial (PEF-Ept)	mole of N eq.	1.23E-03	1.16E-03	2.74E-04	0.00E+00	2.26E-04	2.89E-03	-2.20E-05
Human toxicity, cancer (PEF-CTUh-c)	CTUh	1.60E-07	1.92E-13	3.65E-09	0.00E+00	6.28E-12	1.63E-07	-1.62E-11
Human toxicity, non-cancer (PEF-CTUh-nc)	CTUh	1.26E-09	3.91E-11	1.41E-10	0.00E+00	8.74E-11	1.52E-09	-6.01E-11
Ionising radiation, human health (PEF-IR)	kg Bq U235 eq.	1.41E+00	2.68E-05	4.97E-03	0.00E+00	3.61E-04	1.42E+00	-4.60E-05
Land use (PEF-LU)	No dimension	4.70E-02	0.00E+00	1.30E-03	0.00E+00	1.42E-02	6.25E-02	-7.53E-02
Ozone depletion (PEF-ODP)	kg CFC-11 eq.	6.10E-09	1.68E-11	4.30E-10	0.00E+00	8.66E-10	7.41E-09	-1.05E-10
Photochemical ozone formation - human health (PEF-POCP)	kg of NMVOC eq.	3.74E-04	2.99E-04	6.33E-05	0.00E+00	5.20E-05	7.88E-04	-9.62E-06
Resource use, fossils (PEF-ADPf)	MJ	2.45E+00	1.64E-01	3.14E-01	0.00E+00	8.76E-02	3.01E+00	-2.21E-02
Resource use, minerals and metals (PEF- ADPe)	kg Sb eq	2.08E-08	4.62E-10	8.00E-10	0.00E+00	1.43E-08	3.64E-08	-3.10E-08
Water use (PEF-WU)	m3 eq.	3.10E-02	4.26E-05	2.73E-03	0.00E+00	7.73E-01	8.07E-01	-4.96E-01

#### Resource use indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Net use of fresh water	m <sup>3</sup>	9.16E-04	9.91E-07	6.35E-05	0.00E+00	2.37E-02	2.47E-02	-1.24E-02
Total use of primary energy	MJ	3.01E+00	1.64E-01	3.56E-01	0.00E+00	9.32E-02	3.62E+00	-3.41E-02
Total use of non renewable primary energy resources	MJ	2.45E+00	1.64E-01	3.14E-01	0.00E+00	8.76E-02	3.01E+00	-2.21E-02
Total use of renewable primary energy resources	MJ	5.59E-01	2.09E-04	4.20E-02	0.00E+00	5.58E-03	6.07E-01	-1.20E-02
Use of non-renewable primary energy, excluding non renewable primary energy resources used as raw materials	MJ	2.00E+00	1.64E-01	3.14E-01	0.00E+00	8.76E-02	2.57E+00	-2.21E-02
Use of non-renewable primary energy resources as raw materials	MJ	4.42E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.42E-01	0.00E+00
Use of non-renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	kg	1.30E-02	2.09E-04	4.20E-02	0.00E+00	5.58E-03	6.07E-02	-1.20E-02
Use of renewable primary energy resources as raw materials	MJ	5.46E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.46E-01	0.00E+00
Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of secondary materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

#### Waste category indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Hazardous waste disposed	kg	9.69E-03	0.00E+00	8.07E-04	0.00E+00	4.27E-21	1.05E-02	0.00E+00
Non-hazardous waste disposed	kg	6.07E-02	3.95E-04	1.38E-02	0.00E+00	2.00E-06	7.48E-02	0.00E+00
Radioactive waste disposed	kg	2.77E-05	2.74E-07	1.65E-06	0.00E+00	1.42E-09	2.96E-05	0.00E+00

#### Output flow indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	3.52E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.52E-04	0.00E+00
Materials for energy recovery	kg	4.76E-04	0.00E+00	2.82E-03	0.00E+00	0.00E+00	3.30E-03	0.00E+00
Materials for recycling	kg	4.10E-04	0.00E+00	1.07E-04	0.00E+00	0.00E+00	5.17E-04	0.00E+00

#### **Biogenic carbon content**

Packaging	Unit	Cardboard	Paper	Wood	Sum
Biogenic carbon content (ratio)	%	2.80E+01	3.78E+01	3.95E+01	
Mass	kg	2.21E-02	8.81E-03	1.05E-03	3.20E-02
Biogenic carbon content (declared unit)	kg of C	6.19E-03	3.33E-03	4.13E-04	9.94E-03
Biogenic carbon content (functional unit)	kg of C	6.19E-03	3.33E-03	4.13E-04	9.94E-03
Source		ADEME	APESA/RECORD	EN 16485	

Product	Unit Cardboard		Paper	Wood	Sum
Mass	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content (declared unit)	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content (functional unit)	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00

# **Extrapolation rules**

Extrapolation rules for each phase of the life cycle :

Reference	Manufacturing	Distribution	Installation	Use	End of Life	Module-D
HWY089H	1	1	1	0	1	1
HWY089HSA	1	1	1	0	1	1
HWY090H	1.26	1.12	1	0	2.67	3.51
HWY090HSA	1.26	1.12	1	0	2.67	3.51

This given PEP is done for push button cover without ACB. To have the environemental impact of an ACB with its push button cover, please make the sum of the environemental impacts of each phases of the ACB and the push button cover.

## Verification

Registration N°: HAGE-00836-V01.01-EN	Drafting Rules	PEP-PCR-ed4-2021 09 06					
Registration N . HAGE-00830-V01.01-EN	Supplemented by	No PSR					
Verifier accreditation N°: VH36	Information and reference documents: www.pep-ecopassport.org						
Date of issue: 6-2024	Validity period: 5 years						
Independent verification of the declaration and data, in compliance with ISO 14025 : 2006							
Internal • External o							
The PCR review was conducted by a panel of experts chaired by Julie Orgelet	t (DDemain)						
PEPs are compliant with XP C08-100-1:2016 or EN 50693:2019 The elements of the present PEP cannot be compared with elements from another program.							
The elements of the present PEP cannot be compared with elements from another program. Document in compliance with ISO 14025 : 2006 « Environmental labels and declarations. Type III environmental declarations »							

Nota : The picture has no contractual value. All numerical values indicated in this document may vary and depend of many factors such as the tolerance related to materials, the usage and environment conditions of the products, installation characteristics ... , real values for a product in a concrete application may therefore change. The usage time mentioned in this document is an average duration chosen for the need of the calculations. This value cannot be assimilated to the minimum, average or real life time. The responsibility of the company, issuing this document, can never be engaged if differences would be noticed between the values given by this document and real ones, whatever the causes and/or consequences would be.