







Twin switched socket

Twin switch socket, a delight on the wall, convenient, and beautiful.





Expert Tips

01

Exquisite design

With fine craft, designed precisely, only for the purpose of providing abundant wiring space and convenient installation means.



:hager

02 Delicate chamfering

Good design lies in every detail. Creative and delicate idea brings excellence to our living and working spaces.

03 Multicolor options

Many choices to fit your ideas: white, noble bronze and knight black.





Switch equipped with fluorescent indicator

The switch is dotted with rays of light like twinkling stars, waiting quietly for its guests to enter. Responding to your fingertip, it makes the home bright.



05

IP55 waterproof cover

Ensuring safety against water and dust ingress when operating in wet and dusty areas.

06

USB charger

4.2A, 5V charger with 1 Type C and 2 Type A port suits most portable electronic devices. No need for extra charger, with only USB cables. Up to 3 devices can be charged simultaneously. Easy and convenient to use.





07 The unique brand

Individuality need not to be displayed but it is an expression of your character. The hager brand is exquisitely and uniquely located on the side, offering the product boundless space for expression and letting the essence of beauty blend with the quality of life.



Consistent in size 08

In accordance with the highest standard, the switch and socket are consistent in size, offering flexible interchange-ability.



09

13A 3 pin socket with USB charger

The socket is equipped with two 2.4A USB chargers, which intelligently adapt to mobile devices with different power consumptions, ensuring safety and fast charging.



10

Quick installation

The mounting bracket has superior strength and rigidity. It is suitable for all kinds of installation conditions.



U type screwed terminals

Capacity of terminal can fit 3 x 4mm² flexible/ rigid cable. However, it is easy for wiring and faster for installation.





12

16AX reliable and high performance

Mechanical switch Rated current: 16AX

Rated current: 16AX Rated Power: 4000W

The load capacity of switch is stronger, for better performance in increasing demanding installation.



Delayed power off is built-in, which save power in a smart way. The insert tag switch has LED indicator, which makes it easy for you to find the slot in the dark. After power on, the indicator will turn off automatically.



- Complies with BS EN 60669-1 IEC 60669-1 CB certificate
- 'AX' rated No need to derate
- 16 AX (200W Self Ballasted Lamp (SBL))
- Supplied with M3.5 x 37 mm long fixin g screws

16AX, 3 gang 2 way

16AX, 4 gang 1 way

16AX, 4 gang 2 way

10

10

10

WGCL132F

WGCL141F

WGCL142F

WGCXL132FNB

WGCXL141FNB

WGCXL142FNB

WGCXL132FKB

WGCXL141FKB

WGCXL142FKB

- Capacity of each terminal: 3 x 1.5 mm²
- 2 X 2.5 mm²
- Two way switches can be wired either 1 way or 2 way
- Terminal markings denote:

L1 = one way L2 = two way С = common

- Material: Polycarbonate

for fluoresc	ent loads					.,
		Description	Pack qty.	Cat. Ref. White	Cat. Ref. Noble Bronze	Cat. Ref Knight Black
		Large dolly switch 16AX, 1 gang 1 way	10	WGCL111	WGCXL111NB	WGCXL111KB
		16AX, 1 gang 2 way	10	WGCL112	WGCXL112NB	WGCXL112KB
WGCL111 WGCL112	WGCL121 WGCL122	16AX, 2 gang 1 way	10	WGCL121	WGCXL121NB	WGCXL121KB
		16AX, 2 gang 2 way	10	WGCL122	WGCXL122NB	WGCXL122KB
		16AX, 3 gang 1 way	10	WGCL131	WGCXL131NB	WGCXL131KB
Weeklast	W001444	16AX, 3 gang 2 way	10	WGCL132	WGCXL132NB	WGCXL132KB
WGCL131 WGCL132	WGCL141 WGCL142	16AX, 4 gang 1 way	10	WGCL141	WGCXL141NB	WGCXL141KB
		16AX, 4 gang 2 way	10	WGCL142	WGCXL142NB	WGCXL142KB
10						
		Large dolly switch v	vith flu	orescence		
		16AX, 1 gang 1 way	10	WGCL111F	WGCXL111FNB	WGCXL111FKB
		16AX, 1 gang 2 way	10	WGCL112F	WGCXL112FNB	WGCXL112FKB
WGCL111F WGCL112F	WGCL121F WGCL122F	16AX, 2 gang 1 way	10	WGCL121F	WGCXL121FNB	WGCXL121FKB
		16AX, 2 gang 2 way	10	WGCL122F	WGCXL122FNB	WGCXL122FKB
		16AX, 3 gang 1 way	10	WGCL131F	WGCX L131FNB	WGCXL131FKB



WGCL131F

WGCL132F

WGCR111 WGCR121

WGCL141F

WGCL142F

WGCR122



WGCR112

WGCR131 WGCR132

Round switch 16AX, 1 gang 1 way	10	WGCR111	WGCXR111NB	WGCXR111KB
16AX, 1 gang 2 way	10	WGCR112	WGCXR112NB	WGCXR112KB
16AX, 2 gang 1 way	10	WGCR121	WGCXR121NB	WGCXR121KB
16AX, 2 gang 2 way	10	WGCR122	WGCXR122NB	WGCXR122KB
16AX, 3 gang 1 way	10	WGCR131	WGCXR131NB	WGCXR131KB
16AX, 3 gang 2 way	10	WGCR132	WGCXR132NB	WGCXR132KB



- Complies with BS EN 60669-1 IEC 60669-1 CB certificate
- 10 AX (100W Self Ballasted Lamp (SBL))
- Supplied with M3.5 x 37 mm long fixing screws
- Capacity of each terminal: 3 x 1.5 mm² 2 x 2.5 mm²
- Material: polycarbonate

		Description	Pack qty.	Cat. Ref. White	Cat. Ref. Noble Bronze	Cat. Ref Knight Black
		Large dolly s 10AX, 1 gang intermediate	switch 10	WGCL113	WGCXL113NB	WGCXL113KB
WGCL113	WGCL111B	10A, 1 gang bell switch mark bell syn	10 nbol	WGCL111B	WGCXL111BNB	WGCXL111BKB
WGCL111E		10A, 1 gang press switch mark "EXIT"	10	WGCL111E	WGCXL111ENB	WGCXL111EKB
		Press switch		W001444D		WOON ALLEYD
PRESS	PRESS PRESS	10A, 1 gang	10	WGCL111P	WGCXL111PNB	WGCXL111PKB
WGCL111P	WGCL121P	10A, 2 gang	10	WGCL121P	WGCXL121PNB	WGCXL121PKB
		10A, 3 gang	10	WGCL131P	WGCXL131PNB	WGCXL131PKB
PRESS PRESS	PRICE PRICE PRICE PRICE	10A, 4 gang	10	WGCL141P	WGCXL141PNB	WGCXL141PKB
WGCL131P	WGCL141P					
		Press round 10A, 1 gang	switch	ı WGCR111P	WGCXR111PNB	WGCXR111PKB
WGCR111P	WGCR121P	10A, 2 gang	10	WGCR121P	WGCXR121PNB	WGCXR121PKB
	352	10A, 3 gang	10	WGCR131P	WGCXR131PNB	WGCXR131PKB

Hager Inspire

WGCR131P

Dimmer and fan controller switches

- Complies with BS EN 60669-2-1 IEC 60669-2-1
- Supplied with M3.5 x 37 $_{\mbox{\scriptsize mm}}$ long fixing screws
- Capacity of each terminal: 3 x 1.5 mm²
- Material: Polycarbonate

WGCEFR250



- Pack Cat. Ref. Description
- Cat. Ref.

Noble

Bronze

Cat. Ref Knight Black



250VA, single 6

single, 2 way

WGCEFR250

WGCXEFR250NB

WGCXEFR250KB

Dimmer 40-500W 6

WGCEDR500

WGCXEDR500NB

WGCXEDR500KB

qty. White



- Material: Polycarbonate

- Complies with BS EN 60669-1 IEC 60669-1 CB certificate

WGCL2D1

- 20 AX (250W Self Ballasted Lamp (SBL))

- Supplied with M3.5 x 37 mm long fixing screws

- Capacity of each terminal: 20AX

L, N, E: 2 x 4 mm²

32A, 45A

 $L, N : 2.5 \text{ mm}^2 \sim 16 \text{ mm}^2$ $E \ x \ 2$: $2.5 \ mm^2 \sim 16 \ mm^2$

Cat. Ref Cat. Ref. Description Pack Cat. Ref. Noble Knight qty. White Bronze Black

DP switch

20AX, 1 gang 10 WGCL2D1 WGCXL2D1NB WGCXL2D1KB WGCXL2D2NB 20AX, 2 gang 10 WGCL2D2 WGCXL2D2KB

Remark: Grey reference product - coming soon

WGCL2D2

WGCL2D1N WGCL2D2N WGCL2D12N

DP switch with LED 20AX, 1 gang 10 WGCL2D1N WGCXL2D1NKB WGCXL2D1NNB WGCXL2D2NKB WGCL2D2N 20AX, 2 gang 10 WGCXL2D2NNB

WGCXL2D12NKB 20AX, 1 gang 10 WGCL2D12N WGCXL2D12NNB 2 way

Special marks Abbreviation "AIR CONDITONER" AC "DISH WASHER" DW "DRYER" DR "FRIDGE" FR

Special marks Abbreviation Special marks Abbreviation "HOB" НВ "WASHER" ws "HOOD" HD "WASHING MACHINE" WM "MICROWAVE" MW "WATER HEATER" WH "OVEN" OV

Example: "WATER HEATER" WH 20AX 1 gang WGCL2D1WH

WGCXL2D1NBWH WGCXL2D1KBWH





WGCR45D1

Control switch with LED 32A DP WGCR32D1 WGCXR32D1NB WGCXR32D1KB WGCR45D1 45A DP 8 WGCXR45D1NB WGCXR45D1KB



- Complies with BS 547 (5A sockets) SS 472 (5A sockets) IEC 60884-1 (10A socket)
- Supplied with M3.5 x 37 $_{\mbox{\scriptsize mm}}$ long fixing screws
- Capacity of each terminal: L, N, E: 3 X 2.5 mm² or 2 X 4.0 mm²
- Integral rocker design of switched sockets provides clear red 'on' indication
- Material: Polycarbonate

		Description	Pack qty.	Cat. Ref. White	Cat. Ref. Noble Bronze	Cat. Ref Knight Black
		Socket outle 5A round pin switched	10	WGCS105S	WGCXS105SNB	WGCXS105SKB
WGCS105S	WGCS110US	10A 2 pin switched	10	WGCS110US	WGCXS110USNB	WGCXS110USKB

Remark: Grey reference product - coming soon

Hager Inspire

13A socket outlets

- Complies with BS 1363-2 SS 145-2		- Supplied long fixing			- USB output current 2.4A (Max)	- Material: Polycarbonate
00 143-2		- Capacity L, N, E : 3 2		nm² Or	 Integral rocker desig switched sockets proclear red 'on' indicat 	ovides
		Description	Pack qty.	Cat. Ref. White	Cat. Ref. Noble Bronze	Cat. Ref Knight Black
		13A single	10	WGCS113	WGCXS113NB	WGCXS113KB
		13A single switched	10	WGCS113S	WGCXS113SNB	WGCXS113SKB
WGCS113	WGCS113S	13A single switched w/ LED	10	WGCS113N	WGCXS113NNB	WGCXS113NKB
•	Same Same Same Same Same Same Same Same	13A single switched + 2 x USB c	8 hargers	WGCS113SUSB	WGCXS113SUSBNB	WGCXS113SUSBKB
WGCS113N	WGCS113SUSB	13A twin	14	WGCS213	WGCXS213NB	WGCXS213KB
	. 00	13A twin switched	14	WGCS213S	WGCXS213SNB	WGCXS213SKB
WGCS213	WGCS213S	13A twin switched w/ LED	14	WGCS213N	WGCXS213NNB	WGCXS213NKB
		13A twin switched + 2 x USB c	10 hargers	WGCS213SUSB	WGCXS213SUSBNB	WGCXS213SUSBKB
WGCS213N	WGCS213SUSB					

Remark: Grey reference product - coming soon





- Complies with BS 546 (15A socket) SS 472 (15A socket) IEC 60884-1 (16A German socket)
- Supplied with M3.5 x 37 $_{\mbox{\scriptsize mm}}$ long fixing screws
- Capacity of each terminal: L, N, E: 3 X 2.5 mm² or 2 X 4.0 mm²
- USB output current 2.4A (Max)
- Material: Polycarbonate

- Integral rocker design of switched sockets provides clear red 'on' indication

Pack Cat. Ref. Cat. Ref. Cat. Ref Description Knight qty. White Noble Black Bronze **WGCS115S** WGCXS115SNB WGCXS115SKB 15A 10





round pin switched

16A German socket w/ shutter

WGCS116S 8

WGCXS116SNB WGCXS116SKB



-	Supplied w	∕ith	M3.5	x 37	mm
	long fixing	scr	ews		

- Material: Polycarbonate

long fixing scre	5W3					
				Cat. Ref. White	Cat. Ref. Noble Bronze	Cat. Ref Knight Black
		RJ11 outlet				
28	28 28	1 mod 1	10	WGCT1RJ	WGCXT1RJNB	WGCXT1RJKB
		2 mod 1	10	WGCT2RJ	WGCXT2RJNB	WGCXT2RJKB
CT1RJ	WGCT2RJ					
В		RJ45 outlet lo		e plate WGCT1RJ6LP	WGCXT1RJ6LPNB	WGCXT1RJ6LPKB
		1 mod 2	20	WGCT1RJ6LPNM	WGCXT1RJ6LPNMNB	WGCXT1RJ6LPNMKB
GCT1RJ6LP	WGCT1RJ6LPNM	without symbol				
		2 mod 2	20	WGCT2RJ6LP	WGCXT2RJ6LPNB	WGCXT2RJ6LPKB
			20	WGCT2RJ6LPNM	WGCXT2RJ6LPNMNB	WGCXT2RJ6LPNMKB
GCT2RJ6LP	WGCT2RJ6LPNM	without symbol				
SAT		Accommodat				
TV FM		SMATV plate 3	30	WGCTSMATV	WGCXTSMATVNB	WGCXTSMATVKB
GCTSMATV		RJ45 cat6 out	tlet			
8		1 mod 1	10	WGCT1RJ6	WGCXT1RJ6NB	WGCXT1RJ6KB
		1 mod 1 without symbol	10	WGCT1RJ6NM	WGCXT1RJ6NMNB	WGCXT1RJ6NMKB
GCT1RJ6	WGCT1RJ6NM		4.0	WOOTED IS	W60/707	W00V705 ::::
8 8				WGCT2RJ6	WGCXT2RJ6NB	WGCXT2RJ6KB
		2 mod 1 without symbol	10	WGCT2RJ6NM	WGCXT2RJ6NMNB	WGCXT2RJ6NMKB
GCT2RJ6	WGCT2RJ6NM					
		RJ45 cat5e or		I	WGCXT1RJ5NB	WGCXT1RJ5KB
				WGCT1RJ5	WGCXT2RJ5NB	
GCT1RJ5	WGCT2RJ5	2 mod 1	IU	WGCT2RJ5	WGOATZNJJIND	WGCXT2RJ5KB
		RJ11 + RJ45	cat	5e outlet		
		2 mod 1	10	WGCT2RJRJ5	WGCXT2RJRJ5NB	WGCXT2RJRJ5KB
VGCT2RJRJ5		RJ11 + RJ45 2 mod		6 outlet WGCT2RJRJ6	WGCXT2RJRJ6NB	MCCALOD ID IERD
GCT2RJRJ6		2 1110U	ıU	WGC12NJKJ0	WOONIZHUHUUND	WGCXT2RJRJ6KB
w <u>=</u>	Ţ	TV inlet/outle				
•		2 mod 1	10	WGCT2TVRJ5	WGCXT2TVRJ5NB	WGCXT2TVRJ5KB
GCT2TVRJ5	WGCT1TV	TV inlet/outle		WGCT1TV	WGCXT1TVNB	WGCXT1TVKB
₩ 🖪	TV				WOONTHVIND	WOONTHAND
•	400	TV inlet/outle 2 mod 1		R45 cat6 WGCT2TVRJ6M	WGCXT2TVRJ6NBM	WGCXT2TVRJ6KBM
/GCT2TVRJ6M	WGCT1TVF	TV outlet, F ty	уре			
20121 11 (30)	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	1 mod 1	10	WGCT1TVF	WGCXT1TVFNB	WGCXT1TVFKB
		TV outlet, F ty			W/COVTOTVED ICAIDAA	MOOVEDING
		1 mod 1	IU	WGCT2TVFRJ6M	WGCXT2TVFRJ6NBM	WGCXT2TVFRJ6KBM
GCT2TVFRJ6M					Only white range references	

Remark 1: Separate ordering for single or twin frame is required for all color ranges; Only white range references come in complete set.

Remark 2: Subject to change without prior notice



- Complies with IEC 60669-1 IEC 60669-2-1 IEC 62368-1 (USB) - 16 AX (200W Self Ballasted Lamp (SBL)) - Supplied with M3.5 x 37 $_{\mbox{\scriptsize mm}}$ long fixing screws

- Material: Polycarbonate

		Description		Cat. Ref. White	Cat. Ref. Noble Bronze	Cat. Ref Knight Black
a 01		16AX DND & MUR with LED (Indoor)	10	WGCHDC	WGCXHDCNB	WGCXHDCKB
WGCHDC						
-	*G_*	HDMI+VGA	10	WGCHHIVA	WGCXHHIVANB	WGCXHHIVAKB
WGCHHIVA	WGCS3USB	USB charge USB x 3 (4.2A		WGCS3USB	WGCXS3USBNB	WGCXS3USBKB
- •		USB + 3.5mi	n aud 10	io WGCHUSB35	WGCXHUSB35NB	WGCXHUSB35KB
WGCHUSB35	WGCEE1	Emergency	switch 8	WGCEE1	WGCXEE1NB	WGCXEE1KB
000 C	SHAVERS ONLY	Audio switcl 6W	n 6	WGCEA6	WGCXEA6NB	WGCXEA6KB
WGCEA6	2300 1150	Shaver sock 115/230V	et (wit	th frame for colo WGCHSR	r products) WGCXHSRNB	WGCXHSRKB
	WGCHSR	16A key tag - mechanical	6	WGCHKTM	WGCXHKTMNB	WGCXHKTMKB
WGCHKTM	WGCHKTRFID	16A key tag - RFID	6	WGCHKTRFID	WGCXHKTRFIDNB	WGCXHKTRFIDKB



	Description		Cat. Ref. White	Cat. Ref. Noble Bronze	Cat. Ref Knight Black
	Multi-gang fr	ame			
WGCCH2KB	2 gang horizontal	18	WGCCH2	WGCCH2NB	WGCCH2KB
WGCCV2NB	2 gang vertical	18	WGCCV2	WGCCV2NB	WGCCV2KB
wgccv3	3 gang horizontal	12	WGCCH3	WGCCH3NB	WGCCH3KB
WGCCH3NB	3 gang vertical	12	WGCCV3	WGCCV3NB	wgcсv3кв
WGCCH4	4 gang horizontal	12	WGCCH4	WGCCH4NB	WGCCH4КВ
	5 gang horizontal	9	WGCCH5	WGCCH5NB	WGCCH5KB
WGCCH5KB					
	Blank plate 1 gang	20	WGCBP1	WGCXBP1NB	WGCXBP1KB
WGCBP1					
	Single frame 2 gang	25	WGCC2	WGCC2NB	WGCC2KB
WGCC2 WGCC1S	1 gang square	40	WGCC1S	WGCC1SNB	WGCC1SKB
	1 gang round	40	WGCC1R	WGCC1RNB	WGCC1RKB
WGCC1R WGCVE2	1 gang 2 modules	20	WGCVE2	WWGCVE2NB	WGCVE2KB
	WA covers (T	ransp	arent)		
	IP55 single size	40	XC9003		
	IP55 twin size	40	XC9004		
XC9003 XC9004					
Doorbell					
- Complies with IEC 61558-1 IEC 61558-2-8 IEC 60335-1	XC001 Dimension: 105mm (w) x 10	68mm	(h) x 45mm (d)	Power source: 220-240\ Transformer output: 6\	, , ,
	Description	Pack qty.	Cat. Ref.		
	Doorbell	1	XC001		

XC00

Remark 1: Separate ordering for single or twin frame is required for all color ranges; Only white range references come in complete set. Remark 2: Subject to change without prior notice



Hager Engineering (M) Sdn Bhd K03-10-08, UOA Business Park, No.1 Jalan Pengaturcara U1/51A, 40150 Shah Alam, Selangor, Malaysia

Tel : + (60) 3 5569 0727 Fax : + (60) 3 5569 0728 Email : generalmy@hager.com

hager.com/my

Start your digital journey



Warranty:

A warranty period of 10 years* is offered on Hager products, from date of manufacture, relating to any material or manufacturing defect.

The warranty is void if:

After inspection by Hager technical support department the device is found to have been installed in a manner which is contrary to IEC wiring regulations and accepted practice within the industry at the time of installation.

Warranty does not include damages or scratches caused due to inappropriate cleaning or use of any abrasive material.

An explanation of defect must be included when returning the goods.

^{*} Excludes electronic products, which have a warranty of 2 years.