



Product Environmental Profile

Cylindrical fuse-links for industrial applications 10x38mm gG 2A 500V AC 120kA



Company information

Hager
132 Boulevard d'Europe
F 67215 Obernai Cedex
www.hagergroup.com

References covered

For complete list of the covered references, see details in Appendix.

A question concerning the Product Environmental Profile: info@hager.com

Methodology

PEP has been performed according to the PCR version PEP-PCR-ed4-2021 09 06 and PSR version PSR-0005-ed3.1-2023 12 08 issued by the PEP ecopassport program. For further information, please see the website of the program www.pep-ecopassport.org

Reference product

Reference product identification
LF302G

Functional unit

To protect downstream equipment for 20 years against overloads and short circuits by interrupting the fault current, for a nominal voltage of 500V and a rated current of 2A.

Use scenario based on :

PSR product Category : PSR-0005-ed3.1-2023 12 08

3.15. Other Equipment - Passive product - non-continuous operation

The functional unit is based on the use scenario recommended by the PCR for the category of the reference product.

Materials and substances

All useful measures have been adopted to ensure that the materials used in the composition of the product do not contain any substances banned by the legislation in force at the time of marketing.

Plastics			Metals			Others		
	g	%		g	%		g	%
PE-LD	0.04	0.5%	Copper	2.35	29.5%	Ceramic	3.22	40.4%
			Tin	0.92	11.5%	Cardboard	0.75	9.4%
			Silver	0.03	0.4%	Sand	0.46	5.8%
			Nickel	0.01	<0.1%	Wood	0.19	2.4%
Total mass of reference product with raw material packaging :			7.98 g					
Total mass of reference product (Product + packaging)			7.6 g					

System Boundaries

The environmental information included in the PEP covers all the stages of the life cycle, from "cradle to grave".

Manufacturing		Distribution		Installation		Use							End of life			Module D	
Raw material extraction and processing	Transport to the manufacturer	Manufacturing	Distribution to the place of operation	Installation on the place of operation	Use or application of the product installed	Maintenance	Repair	Replacement	Restoration	Energy requirements during the use stage	Water requirements during the use stage	Deinstallation	Transport to the waste treatment site	Treatment of waste in view of its reuse, recovery and/or recycling	Disposal	Benefits and loads beyond the system boundaries	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
Life cycle stages																	

Manufacturing

These products are manufactured by a site that has received an environmental certification ISO 14001.

This phase takes into account raw materials, manufacturing processes, production offcuts and their end-of-life treatment, upstream transport of materials and sub-assemblies to the manufacturing site, and transport from the manufacturing site to the final logistics platform.

Distribution

The packaging has been designed in accordance with current regulations. In particular, the European directive 94/62/CE relative to packaging and packaging waste.

The used packaging is 100% recyclable or recoverable. Packaging and logistic flows are continuously improved in order to reduce their impact.

This phase taken into account the transport of the finished product, including packaging, to its place of use.

Installation

Installation processes

The processes to install the product are not considered in this study because of their weak impact compared to the other life cycles steps.

This phase only take into account the impact of the packaging waste treatment.

Installation elements (non delivered with the product)

Elements non delivered with the product and needed to install the product are not considered.

Use

Power loss / load dependent				Power consumption / not load dependent			
Active mode		Inactive mode		Active Sleep phase		Passive Sleep phase	
Watt	% of time	Watt	% of time	Watt	% of time	Watt	% of time
0.054	30.0%	0	70.0%	0	0.0%	0	0.0%

This corresponds to a total energy consumption of 2.84 kWh for the use span of 20 years.

Energy model of the use phase :

Europe

Consumables and maintenance :

None

End of life

Considering the complexity of the recycling channels for electric and electronic equipment impacts, we rely mainly on ESR modules (datasets for WEEE product end of life).

The recycling potential of the product is: 6%. The calculation of this rate is based on the method of the IEC/TR 62635.

Environmental impacts

Evaluation of the environmental impact covers the following life cycle stages: raw materials + manufacturing (RMM), distribution (D), installation (I), use (U) and end of life (EoL).

All calculations are done with EIME software version 6.3.2-4 with the database version CODDE-2025-04 .

Indicators set : Indicators for PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0

PEP representative of the covered products marketed in: Europe

Energy models considered for each phase

Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4
Europe	-	Europe	Europe	Europe

Environmental impact indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Acidification (PEF-AP)	mole H+ eq.	6.15E-04	1.99E-06	2.06E-06	6.00E-03	4.80E-06	6.63E-03	0.00E+00
Climate change - Total (PEF-GWP)	kg CO2 eq.	3.54E-02	1.26E-03	1.63E-03	1.15E+00	2.05E-02	1.21E+00	0.00E+00
Climate change-Biogenic (PEF-GWPb)	kg CO2 eq.	2.39E-04	5.17E-09	9.79E-04	2.53E-02	1.36E-10	2.66E-02	0.00E+00
Climate change-Fossil (PEF-GWPf)	kg CO2 eq.	3.52E-02	1.26E-03	6.53E-04	1.12E+00	2.05E-02	1.18E+00	0.00E+00
Climate change-Land use and land use change (PEF-GWP _{lu})	kg CO2 eq.	1.08E-09	1.91E-09	4.84E-12	0.00E+00	5.02E-11	3.05E-09	0.00E+00
Ecotoxicity, freshwater (PEF-CTUe)	CTUe	2.32E-01	3.68E-02	9.20E-03	1.72E+00	5.76E-01	2.57E+00	0.00E+00
EF-particulate Matter (PEF-PM)	Incidence of diseases	4.92E-09	1.71E-11	1.21E-11	4.70E-08	1.41E-11	5.20E-08	0.00E+00
Eutrophication, freshwater (PEF-Epf)	kg P eq.	3.99E-07	4.72E-09	9.02E-09	2.75E-06	1.57E-07	3.32E-06	0.00E+00
Eutrophication, marine (PEF-Epm)	kg N eq.	3.41E-05	3.61E-07	8.44E-07	7.03E-04	3.08E-06	7.41E-04	0.00E+00
Eutrophication, terrestrial (PEF-Ept)	mole of N eq.	4.11E-04	3.97E-06	6.20E-06	1.13E-02	2.46E-05	1.17E-02	0.00E+00
Human toxicity, cancer (PEF-CTUh-c)	CTUh	1.22E-09	2.47E-13	7.20E-11	1.42E-10	5.51E-09	6.95E-09	0.00E+00
Human toxicity, non-cancer (PEF-CTUh-nc)	CTUh	5.56E-09	4.72E-12	1.99E-12	3.36E-09	6.90E-10	9.61E-09	0.00E+00
Ionising radiation, human health (PEF-IR)	kg Bq U235 eq.	8.19E-01	4.47E-05	9.39E-05	1.50E+00	3.99E-06	2.32E+00	0.00E+00
Land use (PEF-LU)	No dimension	4.98E-04	5.40E-06	2.17E-06	3.04E-02	1.42E-07	3.09E-02	0.00E+00
Ozone depletion (PEF-ODP)	kg CFC-11 eq.	2.18E-09	1.53E-11	9.57E-12	4.91E-09	1.46E-11	7.13E-09	0.00E+00
Photochemical ozone formation - human health (PEF-POCP)	kg of NMVOC eq.	1.36E-04	1.28E-06	1.41E-06	2.23E-03	5.58E-06	2.37E-03	0.00E+00
Resource use, fossils (PEF-ADPf)	MJ	1.76E+00	2.24E-02	6.74E-03	2.75E+01	3.32E-03	2.93E+01	0.00E+00
Resource use, minerals and metals (PEF-ADPe)	kg Sb eq	4.59E-05	4.50E-10	3.44E-11	3.72E-07	2.02E-11	4.63E-05	0.00E+00
Water use (PEF-WU)	m3 eq.	2.19E-02	4.54E-05	5.69E-05	8.70E-02	3.12E-04	1.09E-01	0.00E+00

Resource use indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Net use of fresh water	m3	5.11E-04	1.06E-06	4.37E-06	2.03E-03	7.26E-06	2.56E-03	0.00E+00
Total primary energy	MJ	1.95E+00	2.25E-02	7.65E-03	3.40E+01	3.32E-03	3.59E+01	0.00E+00
Total non renewable primary energy	MJ	1.76E+00	2.24E-02	6.74E-03	2.75E+01	3.32E-03	2.93E+01	0.00E+00
Total renewable primary energy	MJ	1.82E-01	7.07E-05	9.06E-04	6.44E+00	2.41E-06	6.62E+00	0.00E+00
Non renewable primary energy used as energy	MJ	1.75E+00	2.24E-02	6.74E-03	2.75E+01	3.32E-03	2.93E+01	0.00E+00
Non renewable primary energy used as raw material	MJ	1.56E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.56E-02	0.00E+00
Use of non renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renewable primary energy used as energy	MJ	1.65E-01	7.07E-05	9.06E-04	6.44E+00	2.41E-06	6.61E+00	0.00E+00
Renewable primary energy used as raw material	MJ	1.71E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.71E-02	0.00E+00
Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of secondary material	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Waste category indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Hazardous waste disposed	kg	3.58E-01	5.28E-06	3.65E-05	3.17E-02	7.00E-03	3.97E-01	0.00E+00
Non hazardous waste disposed	kg	4.44E-03	1.17E-04	1.89E-04	1.73E-01	9.79E-06	1.78E-01	0.00E+00
Radioactive waste disposed	kg	1.72E-06	9.28E-08	4.29E-08	4.07E-05	6.30E-09	4.26E-05	0.00E+00

Output flow indicators

Indicators	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End Of Life C1-C4	GLOBAL	Module D
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for energy recovery	kg	8.30E-05	0.00E+00	5.40E-05	0.00E+00	0.00E+00	1.37E-04	0.00E+00
Materials for recycling	kg	1.61E-04	0.00E+00	4.92E-04	0.00E+00	0.00E+00	6.53E-04	0.00E+00

Biogenic carbon content

Packaging	Unit	Cardboard	Paper	Wood	Sum
Biogenic carbon content (ratio)	%	2.80E+01	3.78E+01	3.95E+01	
Mass	kg	7.52E-04	0.00E+00	1.90E-04	9.42E-04
Biogenic carbon content (declared unit)	kg of C	2.11E-04	0.00E+00	7.51E-05	2.86E-04
Biogenic carbon content (functional unit)	kg of C	2.11E-04	0.00E+00	7.51E-05	2.86E-04
Source		ADEME	APESA/RECORD	EN 16485	

Product	Unit	Cardboard	Paper	Wood	Sum
Mass	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content (declared unit)	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content (functional unit)	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Extrapolation rules

The extrapolation rules are based on weight for all life cycle phases except the use phase. For the use phase, extrapolation is based on total power consumption. Extrapolation table is presented in appendix.

Verification

Registration N°: HAGE-01437-V01.02-EN	Drafting Rules	PEP-PCR-ed4-2021 09 06		
	Supplemented by	PSR-0005-ed3.1-2023 12 08		
Verifier accreditation N°: VH65	Information and reference documents: www.pep-ecopassport.org			
Date of issue: 11-2025	Validity period: 5 years			
Independent verification of the declaration and data, in compliance with ISO 14025 : 2006				
Internal <input checked="" type="radio"/> External <input type="radio"/>				
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDomain)				
PEPs are compliant with XP C08-100-1:2016 or EN 50693:2019				
The elements of the present PEP cannot be compared with elements from another program.				
Document in compliance with ISO 14025 : 2006 « Environmental labels and declarations. Type III environmental declarations »				

Nota :

The picture has no contractual value.
All numerical values indicated in this document may vary and depend of many factors such as the tolerance related to materials, the usage and environment conditions of the products, installation characteristics ... , real values for a product in a concrete application may therefore change.

The usage time mentioned in this document is an average duration chosen for the need of the calculations. This value cannot be assimilated to the minimum, average or real life time.

The responsibility of the company, issuing this document, can never be engaged if differences would be noticed between the values given by this document and real ones, whatever the causes and/or consequences would be.



COMMERCIAL REFERENCE	WEIGHT / pc (in g)	Manufacturing A1-A3	Distribution A4	Installation A5	Use B1-B7	End of life C1-C4
LF302G	7.00	1.06	1.06	1.06	1.09	1.06
LF310M	6.60	1.00	1.00	1.00	1.00	1.00
LF310PV2	7.00	1.06	1.06	1.06	4.69	1.06
LF312G	6.50	0.98	0.98	0.98	2.36	0.98
LF312PV2	1.00	0.15	0.15	0.15	4.73	0.15
LF315PV1	1.00	0.15	0.15	0.15	4.44	0.15
LF316G	6.50	0.98	0.98	0.98	2.91	0.98
LF316M	7.50	1.14	1.14	1.14	1.67	1.14
LF316PV2	7.00	1.06	1.06	1.06	4.91	1.06
LF320G	6.50	0.98	0.98	0.98	3.64	0.98
LF320M	6.50	0.98	0.98	0.98	1.75	0.98
LF320PV2	7.00	1.06	1.06	1.06	5.27	1.06
LF325G	6.50	0.98	0.98	0.98	4.73	0.98
LF325M	6.50	0.98	0.98	0.98	2.55	0.98
LF325PV1	1.00	0.15	0.15	0.15	4.98	0.15
LF332G	7.50	1.14	1.14	1.14	5.27	1.14
LF332M	7.00	1.06	1.06	1.06	3.27	1.06
LF332PV1	1.00	0.15	0.15	0.15	8.00	0.15
LF332PV1	1.00	0.15	0.15	0.15	8.00	0.15
LF410G	18.50	2.80	2.80	2.80	2.36	2.80
LF416G	18.50	2.80	2.80	2.80	3.64	2.80
LF420G	18.50	2.80	2.80	2.80	4.54	2.80
LF425G	18.50	2.80	2.80	2.80	6.00	2.80
LF432G	18.30	2.77	2.77	2.77	6.36	2.77
LF440G	17.50	2.65	2.65	2.65	8.64	2.65
LF450G	0.02	0.00	0.00	0.00	8.73	0.00
LF525G	51.00	7.73	7.73	7.73	6.00	7.73
LF532G	51.00	7.73	7.73	7.73	6.36	7.73
LF540G	51.00	7.73	7.73	7.73	7.27	7.73
LF550G	51.00	7.73	7.73	7.73	10.00	7.73
LF563G	51.00	7.73	7.73	7.73	12.54	7.73
LF580G	51.00	7.73	7.73	7.73	14.18	7.73
LF590G	20.50	3.11	3.11	3.11	16.36	3.11
LF599G	51.00	7.73	7.73	7.73	20.73	7.73
LF300G	7.00	1.06	1.06	1.06	7.22	1.06
LF301G	7.00	1.06	1.06	1.06	13.99	1.06
LF301M	7.00	1.06	1.06	1.06	0.50	1.06
LF302M	7.00	1.06	1.06	1.06	0.91	1.06
LF304G	7.00	1.06	1.06	1.06	3.53	1.06
LF304M	7.00	1.06	1.06	1.06	1.57	1.06
LF304M	7.00	1.06	1.06	1.06	1.57	1.06
LF306G	6.36	0.96	0.96	0.96	4.29	0.96
LF306M	6.36	0.96	0.96	0.96	1.62	0.96
LF308G	7.00	1.06	1.06	1.06	3.79	1.06
LF308M	6.36	0.96	0.96	0.96	2.63	0.96
LF310G	6.36	0.96	0.96	0.96	5.05	0.96