



Technical Features

Rated current	6 A
---------------	-----

Type of connection	Screw terminal
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

Number of modules	0.50
-------------------	------

Type of contacts	1NC+1NO
------------------	---------

Voltage	
Rated insulation voltage U_i	4000 V
Type voltage supply	AC

Number of mechanical operations	12000
---------------------------------	-------

Operating temperature	-25 - 60 °C
-----------------------	-------------

Electric endurance in number of cycles	6000
--	------

Storage/transport temperature	-40 - 80 °C
-------------------------------	-------------

Total power loss under IN	0.10 W
---------------------------	--------

Height	80 mm
--------	-------

Equipment	
Number of INV contacts	0
Number of NC contacts	1

RoHS conform	Yes
--------------	-----

Illustrations | Drawings

