



HHA026Z

**Moulded Case Circuit Breaker x160 4P 25kA 25A**

**Technical Features**

**Electric current**

|   |         |
|---|---------|
| Rated current   | 25 A    |
| Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 400 V AC IEC 60947-2 | 25 kA   |
| Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 240 V AC IEC 60947-2 | 35 kA   |
| Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 690 V AC IEC 60947-2 | 4 kA    |
| Rated current 10°C according to IEC 60947   | 29.30 A |
| Rated current 15°C according to IEC 60947   | 28.80 A |
| Rated current 20°C according to IEC 60947   | 28.30 A |
| Rated current 25°C according to IEC 60947   | 27.70 A |
| Rated current 30°C according to IEC 60947   | 27.20 A |
| Rated current at 35°C according to IEC 60947  | 26.70 A |
| Rated current at 40°C according to IEC 60947  | 26.10 A |
| Rated current 45°C according to IEC 60947   | 25.50 A |
| Rated current 50°C according to IEC 60947   | 25 A    |
| Rated current 55°C according to IEC 60947   | 24.40 A |
| Rated current at 60°C according to IEC 60947  | 23.70 A |
| Rated current 65°C according to IEC 60947   | 23.10 A |
| Rated current 70°C according to IEC 60947   | 22.50 A |

**Architecture**

|                           |                |
|---------------------------|----------------|
| Number of poles           | 4              |
| Control/operation element | Toggle         |
| Device construction type  | Fixed built-in |

**Tripping**

|                            |       |
|----------------------------|-------|
| Response time when opening | 10 ms |
|----------------------------|-------|

**Frequency**

|           |            |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

**Voltage**

|  |             |
|--|-------------|
| Rated impulse withstand voltage U <sub>imp</sub> | 8000 V      |
| Rated insulation voltage U <sub>i</sub>          | 690 V       |
| Rated operational voltage U <sub>e</sub>         | 220 - 415 V |

**Functions**

|           |        |
|-----------|--------|
| Trip unit | TM F/F |
|-----------|--------|

**Power**

|                                       |         |
|---------------------------------------|---------|
| Total power loss under I <sub>N</sub> | 13.70 W |
|---------------------------------------|---------|

**Endurance**

|  |       |
|--|-------|
| Electric endurance in number of cycles | 10000 |
| Number of mechanical operations        | 20000 |

**Safety**

|                               |      |
|-------------------------------|------|
| Ingress Protection (IP) class | IP4X |
|-------------------------------|------|

**Connection**

|                                  |                        |
|----------------------------------|------------------------|
| Cross-section flexible conductor | 4 - 70 mm <sup>2</sup> |
| Cross-section rigid conductor    | 4 - 95 mm <sup>2</sup> |

**Installation, mounting**

|                               |          |
|-------------------------------|----------|
| Nominal tightening torque     | 6 - 6 Nm |
| Mounting-/Connection Position | Front    |

**Connectivity**

|                    |                |
|--------------------|----------------|
| Type of connection | Screw terminal |
|--------------------|----------------|

---

**Settings**

|   |         |
|---|---------|
| Thermal protection knob setting xIN                       | 1       |
|   | 1       |
| Adjustment range short-term delayed short-circuit release | 0 - 0 A |

---

**Compatibility**

|                       |    |
|-----------------------|----|
| Suitable for DIN Rail | No |
|-----------------------|----|

---

**Main electrical attributes**

|                               |          |
|-------------------------------|----------|
| Magnetic protection trip time | 0 - 0 ms |
|-------------------------------|----------|