

Dual Row 4+6 Way 100A Switch 2*100A 30mA RCCB with Knockouts

Technical Features

| Installation, mounting | |
|--|------------------|
| Mounting on | Surface mounting |
| | |
| Architecture Number of poles | |
| realised of poles | |
| Functions | |
| Has protection main switch | Yes |
| Overvoltage protection | Yes |
| Capacity | |
| Number of modules | 10 |
| Electric current | |
| Rated current | 100 A |
| | |
| Dimensions | 100.50 |
| Depth | 102.50 mm |
| Height Width | 480 mm 220 mm |
| Thickness of sidewall | 1 mm |
| THICKIESS OF SIGGRAM | |
| Cover, door | |
| Interlockable | No |
| Door/cover is transparent | No |
| Materials | |
| RAL code | 9010 |
| Colour | Pure white |
| Material | Steel |
| Installation, mounting | |
| Suitable for outdoor usage | No |
| Connection | |
| Number of accessible phases | 1 |
| Scope of delivery | |
| Number of earth leakage circuit breaker type A | 2 |
| Number of RCCB in enclosure | 2 |
| | |
| Equipment | |
| Number of rows Number of rails | 2 2 |
| Extension possible | 2 No |
| Extension possible | NO |
| Safety | |
| Impact resistance IK | IK05 |
| Ingress Protection (IP) class | IP2XC |
| Sustainability | |
| RoHS conform | Yes |