




EE831



**Motion detector infrared 200°, IP55, wall mounted, anthracite**

**Technical Features**

**Detection**

|                 |                   |
|-----------------|-------------------|
| Detection angle | 200 - 200         |
| Type of sensor  | Movement detector |

**Settings**

|            |              |
|------------|--------------|
| Time delay | 5 S - 15 Min |
|------------|--------------|

**Lighting**

|                                |             |
|--------------------------------|-------------|
| Response brightness adjustable | 5 - 1000 lx |
|--------------------------------|-------------|

**Frequency**

|           |            |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

**Dimensions**

|                                 |               |
|---------------------------------|---------------|
| Width                           | 83 mm         |
| Recommended installation height | 2.50 - 2.50 m |

**Use conditions**

|                       |             |
|-----------------------|-------------|
| Operating temperature | -20 - 55 °C |
|-----------------------|-------------|

**Materials**

|          |            |
|----------|------------|
| Colour   | Anthracite |
| Material | Plastic    |

**Safety**

|                               |      |
|-------------------------------|------|
| Ingress Protection (IP) class | IP55 |
|-------------------------------|------|

**Installation, mounting**

|                            |                  |
|----------------------------|------------------|
| Mounting on                | Surface mounting |
| Suitable for outdoor usage | Yes              |

**Texts**

|                    |   |
|--------------------|---|
| Function           | Can be used as a single unit, main device or extension unit     |
| Installation mode  | For wall and ceiling mounting, corner installation with adapter |
| Type of connection | With plug-in terminals  |