Product Datasheet SVN131



Yes



SVN131

Green LED Indicator light 12/48V

Technical Features

RoHS conform

| Capacity | |
|--------------------------------------|---------------------------|
| Number of modules | 1 |
| Frequency | |
| Frequency | 50 - 60 Hz |
| | |
| Voltage | |
| Rated insulation voltage Ui | 250 V |
| Rated impulse withstand voltage Uimp | 2000 V |
| Rated operational voltage Ue | 12 - 48 V |
| Type voltage supply | AC/DC |
| Use conditions | |
| Operating temperature | -20 - 50 °C |
| Storage/transport temperature | -40 - 80 °C |
| Connectivity | |
| Type of connection | Screw terminal |
| Connection | |
| Cross-section flexible conductor | 0.75 - 6 mm² |
| Cross-section rigid conductor | 0.75 - 10 mm ² |
| Oloss-section rigid conductor | 0.73 - 10 111111 |
| Power | |
| Total power loss under IN | 0.33 W |
| Dimensions | |
| Height | 83 mm |
| Width | 17.50 mm |
| Depth | 62 mm |
| Lighting | |
| Type of lamp | LED |
| | |
| Connection Type of lown poplet | Fix |
| Type of lamp socket | FIX |
| Materials | |
| Colour | Green |
| Safety | |
| Ingress Protection (IP) class | IP20 |
| | |
| Power | |
| Power per charging point | 0 kW |
| Sustainability | |
| REACh-SVHC free | Yes |
| Dalifo acustamas | |