Product Datasheet

EE805A



5 - 1000 lx

50 - 60 Hz



EE805A





IP21









Movement detector 360° flush mounted with normally open contact

Technical Features

| - 11 | Ωt | ec | 11 | റ | n |
|------|----|----|----|---|---|
| - | Cι | ᆫ | w | u | ш |
| | | | | | |

| Detection angle | 360 - 360 |
|-----------------|-------------------|
| Type of sensor | Movement detector |
| | Presence detector |
| Settings | |
| Time delay | 5 S - 30 Min |

Lighting Response brightness adjustable

| Frequency | | | |
|-----------|--|--|--|

Frequency

| Dimensions | | |
|---------------------------------|-------------|--|
| Width | 19 mm | |
| Built-in depth | 55 mm | |
| Recommended installation height | 2.5 - 3.5 m | |

Use conditions

| Operating temperature | -5 - 4 | 5 °C |
|-----------------------|---------|------|
| Operating temperature | -0 - 40 | |

Materials

| Colour | White |
|----------|---------|
| Material | Plastic |

Safety

| Ingress Protection (IP) class | IP2 ⁻¹ |
|-------------------------------|-------------------|
|-------------------------------|-------------------|

Installation, mounting

| N | Mounting on | Flush mounting |
|---|----------------------------|----------------|
| 5 | Suitable for outdoor usage | No |

Texts

| Function | Can only be used as individual unit |
|--------------------|--|
| Installation mode | With spring clips for ceiling installation For ceiling mounting |
| Type of connection | With plug-in terminals |