



SBN363

### 3-pole, 63A Modular Switch

#### Technical Features

##### Architecture

Number of poles	3
Neutral position	Without neutral
Type of pole	3P

##### Electric current

Rated current	63 A
Acceptable current rating AC21 category A	63 A
Acceptable current rating AC21 category B	63 A
Acceptable current rating AC22 category A	63 A
Acceptable current rating AC22 category B	63 A
Rated short-circuit making capacity $I_{cm}$ under 415 V AC according to IEC 60947-3	1.33 kA
Rated short-time withstand current $I_{cw}$ 1s IEC 60947	0.94 kA
Rated conditional short-circuit current $I_{nc}$ with fuse according to IEC/EN 6000A/80A gG parallel 32A gG 60669-2-4	

##### Installation, mounting

Nominal tightening torque	2.80 - 2.80 Nm
---------------------------	----------------

##### Voltage

Rated operational voltage $U_e$	400 - 400 V
Type voltage supply	AC
Rated insulation voltage $U_i$	440 V
Rated impulse withstand voltage $U_{imp}$	6000 V

##### Capacity

Number of modules	3
-------------------	---

##### Safety

Ingress Protection (IP) class	IP20
-------------------------------	------

##### Frequency

Frequency	50 - 60 Hz
-----------	------------

##### Dimensions

Height	83 mm
Width	52.50 mm
Depth	68 mm
Dimensions	83 x 52.50 mm

##### Equipment

Number of NO contacts	3
Number of NC contacts	0

##### Use conditions

Operating temperature	-20 - 70 °C
Storage/transport temperature	-40 - 80 °C

##### Connection

Cross-section flexible conductor	2.5 - 16 mm <sup>2</sup>
Cross-section rigid conductor	2.5 - 25 mm <sup>2</sup>

##### Endurance

Number of mechanical operations	60000
Electrical durability at nominal load in AC21 in operating cycles	5000
Electrical durability at nominal load in AC22 in operating cycles	5000

<b>Power</b>	
Total power loss under IN	6.90 W
Power loss per pole at In	2.30 W
<b>Connectivity</b>	
Top connection alignment for modular devices	Aligned terminal
<b>Sustainability</b>	
REACH-SVHC free	Yes
RoHS conform	Yes