



181113



Push-button, NO contact, TS, stainless steel matt, brushed nickel

Technical Features

| Electric current | |
|---------------------------|-------------|
| Momentary contact current | 1.50 A |
| Voltage | |
| Rated voltage | 12 V |
| Architecture | |
| Control/operation element | Push button |

| nated voltage | 1Z V |
|------------------------------------|------------------------------------|
| Architecture | |
| Control/operation element | Push button |
| Number of poles | 1 |
| Materials | |
| Colour | Stainless steel |
| Surface finish | Matt |
| Material | Brass Nickel Stainless steel |
| Treatment | Brushed |
| Transparent | No |
| Dimensions | |
| Height | 22 mm |
| Width | 22 mm |
| Depth | 19.70 mm |
| Built-in depth | 13 mm |
| Built-in depth flush-mounted boxes | 0 mm |
| Controls and indicators | |
| Number of buttons | 1 |
| With feedback signal contact | No |
| Safety | |
| Ingress Protection (IP) class | IP20 |
| Impact resistance IK | IK07 |
| Accessories | |
| Has labelling field | No |
| Use conditions | |

| Number of buttons | 1 |
|-------------------------------|-------------|
| With feedback signal contact | No |
| Safety | |
| Ingress Protection (IP) class | IP20 |
| Impact resistance IK | IK07 |
| Accessories | |
| Has labelling field | No |
| Use conditions | |
| Operating temperature | -20 - 60 °C |

| Texts Imprint | Without imprint |
|--------------------|------------------------|
| Installation mode | For screw fastening |
| Switch mode | Normally open contact |
| Type of connection | With plug-in terminals |

| Yes |
|-----|
| Yes |
| |