



20302089



Thermostat, NC contact, centre plate, rocker switch, R.1/R.3, p. white glossy

Technical Features

Toomingan Foatanoo	
Architecture	
Control/operation element	Rotative
Electric current	
Rated current	4 A
Max. switching current	10 A
Voltage	
Nominal voltage	230-230 V
Power supply	
Supply voltage	230 V AC
Frequency	
Frequency	50 - 60 Hz
Settings	
Comfort temperature setpoint	5 - 30 °C
Materials	D.L. 199
Colour RAL code	Polar white
Surface finish	9010
Material Material	Glossy Metal
Material	Plastic
Treatment	Untreated
Dimensions	
Height	71 mm
Width	71 mm
Depth	47.20 mm
Screen	
With display	No
Equipment	0.50 K
Switching temperature difference	0.50 K
Type of thermostat	Room thermostat
Type of probe With heater	Bimetal Yes
With Heater	165
Safety	
Ingress Protection (IP) class	IP20
Connection	
Type of contacts	1NC
Type or contacts	IIVO
Compatibility	
Type of HVAC control	Heating
Use conditions	
Energy efficiency class	I (1%)
Energy emolency diass	1 (170)
Texts	
Installation mode	Without spreader claws
Type of connection	With screw terminals
Thermal re-circulation	With thermal return
Imprint	With imprint
Junction	With separate connection for night lowering

Product Datasheet 20302089



Sustainability

REACh-SVHC free	Yes
RoHS conform	Yes