



TYA670D

### Gateway KNX/EIB-DALI, 4 modules

#### Technical Features

##### Equipment

|            |     |
|------------|-----|
| Web server | Yes |
|------------|-----|

##### Voltage

|                            |             |
|----------------------------|-------------|
| Operating voltage          | 240 - 240 V |
| Operating voltage over bus | 21 - 32 V   |

##### Connectivity

|  |                             |
|--|-----------------------------|
| Type of interface bus system/media gateway | Light system interface/DALI |
|--|-----------------------------|

##### Settings

|                              |     |
|------------------------------|-----|
| Supported configuration mode | ETS |
|------------------------------|-----|

##### Power

|                      |         |
|----------------------|---------|
| Power consumption VA | 0.15 VA |
|----------------------|---------|

##### Safety

|                               |      |
|-------------------------------|------|
| Ingress Protection (IP) class | IP30 |
|-------------------------------|------|

##### Equipment

|                    |   |
|--------------------|---|
| Number of channels | 1 |
|--------------------|---|

##### Use conditions

|                       |           |
|-----------------------|-----------|
| Operating temperature | 5 - 45 °C |
|-----------------------|-----------|

##### Controls and indicators

|                     |     |
|---------------------|-----|
| With LED indication | Yes |
|---------------------|-----|

##### Dimensions

|                       |            |
|-----------------------|------------|
| Width                 | 72 mm      |
| Dimensions            | 90 x 72 mm |
| Depth                 | 70 mm      |
| Number of width units | 4          |

##### Texts

|                    |  |
|--------------------|--|
| Voltage            | As DALI master and power supply for DALI devices |
| Type of connection | With screw terminals                             |

##### Sustainability

|                 |     |
|-----------------|-----|
| Halogen free    | Yes |
| REACH-SVHC free | Yes |
| RoHS conform    | Yes |