## Product Datasheet WBWP1S



Yes



WBWP1S

## Socket IP53 single horizontal 10A

## **Technical Features**

Electric current	
Rated current	10 A
Voltage	
Nominal voltage	250 - 250 V
Frequency	
Frequency	50 - 50 Hz
Materials Colour	Light grou
Surface finish	Light grey Glossy
Material	Glass
Material	Thermoplastic
Treatment	Untreated
Dimensions	
Height	85 mm
Width	85 mm
Depth	88 mm
Installation, mounting	
Mounting on	Surface mounting
Connectivity	
Type of connection	Screw terminal
Mounting type	Screw mounting
	Colow mounting
Equipment	
Connector/plug type socket outlet	Australian standard AS/NZS 3112
Rotated central insert	No No
With hinged lid	No
With pignal large	No No
With signal lamp	No
Accessories	
Has labelling field	No
Capacity	
Number of modules	1
Safety	
Impact resistance IK	IK08
Ingress Protection (IP) class	IP53
Functions	
With orientation lighting	No
With function lighting	No
vital ranotion lighting	140
Texts	AAPU
Imprint	Without imprint
Cover	Complete housing
Protection Time of connection	Without enhanced contact protection
Type of connection	With screw terminals
Sustainability	
REACh-SVHC free	Yes
D-110 (	

RoHS conform