## **Product Datasheet** GD106E





GD106E

## Mini-enclosure, gamma, 6 module, protect. class IP30, 1xPE

## **Technical Features**

W. II.	
Voltage	000 000 0
Nominal voltage	230 - 230 V
Installation, mounting	
Suitable for outdoor usage	No
Mounting on	Surface mounting
Electric current	50.4
Rated current	50 A
Equipment	
Number of rails	1
Number of rows	1
Number of section in width	1
With lock	No
Has neutral terminal block	No
O-marity.	
Capacity Number of modules	6
Number of modules	
Functions	
Has protection main switch	No
With conduit inlets	Yes
Dimensions	
Height	
Width	146 mm
Depth	82 mm
Берит	02 111111
Cover, door	
Number of locks	0
Dimensions	
Number of width units	6
Training of the first of the fi	
Cover, door	
Door/cover is transparent	No
Connectivity	
Mounting type	Screw mounting
Materials	
Material	Plastic
RAL code	9010
Colour	Pure white
Equipment	
Has earthing terminal block	Yes
Has mounting plate	No
Safety	
Protection class	Isolation class II
Impact resistance IK	IK05
Ingress Protection (IP) class	IP30
Locking type	Without lock
Glow wire test	750 °C
Sustainability	
REACh-SVHC free	Yes
RoHS conform	Yes
	165