



EPE524

### Latching relay 2NO 24V

#### Technical Features

##### Electric current

Rated current	16 A
Quiescent current	6 mA
Acceptable current rating AC1	16 A

##### Capacity

Number of modules	1
-------------------	---

##### Connection

Type of contacts	2NO
Cross-section flexible conductor	1 - 6 mm <sup>2</sup>
Cross-section rigid conductor	1.5 - 10 mm <sup>2</sup>
Number of contacts	2

##### Voltage

Command voltage AC	24 - 24 V
Command voltage DC	12 - 12 V
Command voltage 2	12 - 12 V
Command voltage 1	24 - 24 V
Rated insulation voltage Ui	250 V
Rated operational voltage Ue	250 - 250 V

##### Frequency

Frequency	50 - 60 Hz
-----------	------------

##### Use conditions

Operating temperature	-5 - 40 °C
Storage/transport temperature	-40 - 80 °C

##### Connectivity

Type of connection	Screw terminal
--------------------	----------------

##### Power

Total power loss under IN	2.40 W
Inrush power absorbed	25 VA

##### Dimensions

Height	83 mm
Width	18 mm
Depth	63 mm

##### Lighting

Max. load fluorescent lamp	800 VA
Max. load fluorescent lamp parallel compensated	900 VA

##### Equipment

Number of NO contacts	2
Number of NC contacts	0

##### Sustainability

REACH-SVHC free	Yes
RoHS conform	Yes