



HHJ401GR

**Moulded Case Circuit Breaker h3 x630 LSnl 4P4D N0-50-100% 400A 25kA FTC**

**Technical Features**

**Electric current**

|   |       |
|---|-------|
| Rated current   | 400 A |
| Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 230 V AC IEC 60947-2 | 35 kA |
| Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 240 V AC IEC 60947-2 | 35 kA |
| Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 400 V AC IEC 60947-2 | 25 kA |
| Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 415 V AC IEC 60947-2 | 25 kA |
| Breaking capacity on 1-pole for AC 230 V IEC 60947-2                                      | 10 kA |
| Breaking capacity on 1-pole for AC 400 V IEC 60947-2                                      | 10 kA |

**Architecture**

|                           |                |
|---------------------------|----------------|
| Number of poles           | 4              |
| Control/operation element | Toggle         |
| Device construction type  | Fixed built-in |
| Neutral position          | Left           |

**Tripping**

|                            |       |
|----------------------------|-------|
| Response time when opening | 10 ms |
|----------------------------|-------|

**Electric current**

|   |       |
|---|-------|
| Rated service breaking capacity I <sub>cs</sub> under 230 V AC according to IEC 60947-2 | 35 kA |
| Rated service breaking capacity I <sub>cs</sub> under 400 V AC according to IEC 60947-2 | 25 kA |
| Rated current 10°C according to IEC 60947   | 400 A |
| Rated current 15°C according to IEC 60947   | 400 A |
| Rated current 20°C according to IEC 60947   | 400 A |
| Rated current 25°C according to IEC 60947   | 400 A |
| Rated current 30°C according to IEC 60947   | 400 A |
| Rated current at 35°C according to IEC 60947  | 400 A |
| Rated current at 40°C according to IEC 60947  | 400 A |
| Rated current 45°C according to IEC 60947   | 400 A |
| Rated current 50°C according to IEC 60947   | 400 A |
| Rated current 55°C according to IEC 60947   | 400 A |
| Rated current at 60°C according to IEC 60947  | 400 A |
| Rated current 65°C according to IEC 60947   | 400 A |
| Rated current 70°C according to IEC 60947   | 400 A |

**Settings**

|   |                  |
|---|------------------|
| Ir1 current dial setting                                  | 160 A            |
|   | 180 A            |
|   | 200 A            |
|   | 225 A            |
|   | 250 A            |
|   | 300 A            |
|   | 350 A            |
|   | 370 A            |
|   | 400 A            |
| Adjustment range short-term delayed short-circuit release | 218.4 - 4000.0 A |

**Frequency**

|           |            |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

**Installation, mounting**

|                               |            |
|-------------------------------|------------|
| Nominal tightening torque     | 18 - 18 Nm |
| Mounting-/Connection Position | Front      |

**Voltage**

|  |             |
|--|-------------|
| Rated impulse withstand voltage U <sub>imp</sub> | 8000 V      |
| Rated insulation voltage U <sub>i</sub>          | 800 V       |
| Rated operational voltage U <sub>e</sub>         | 220 - 415 V |

**Functions**

|           |      |
|-----------|------|
| Trip unit | LSNI |
|-----------|------|

**Power**

|                           |        |
|---------------------------|--------|
| Total power loss under IN | 57.8 W |
| Power loss per pole at In | 19.3 W |

**Equipment**

|   |   |
|---|---|
| Number of auxiliary contacts as change-over contact     | 0 |
| Number of auxiliary contacts as normally closed contact | 0 |
| Number of auxiliary contacts as normally open contact   | 0 |

**Safety**

|                               |      |
|-------------------------------|------|
| Ingress Protection (IP) class | IP4X |
|-------------------------------|------|

**Use conditions**

|                       |             |
|-----------------------|-------------|
| Operating temperature | -25 - 70 °C |
|-----------------------|-------------|

**Connection**

|                     |          |
|---------------------|----------|
| Connector/plug type | Terminal |
|---------------------|----------|

**Cable**

|                |        |
|----------------|--------|
| Cable material | Copper |
|----------------|--------|

**Dimensions**

|        |        |
|--------|--------|
| Height | 260 mm |
| Width  | 185 mm |
| Depth  | 150 mm |

**Controls and indicators**

|                        |    |
|------------------------|----|
| Motor drive integrated | No |
|------------------------|----|

**Compatibility**

|                                 |     |
|---------------------------------|-----|
| Suitable for DIN Rail           | No  |
| Compatible with RDC AOB         | Yes |
| Suitable for distribution board | Yes |

**Power supply**

|                       |               |
|-----------------------|---------------|
| Position power supply | Bidirectional |
|-----------------------|---------------|

**Electrical protection**

|   |        |
|---|--------|
| Long-time overload protection (ltd): delay (tr)         | 5 s    |
| Short-time protection (std): current (Isd)              | 1.5    |
|   | 2      |
|   | 3      |
|   | 4      |
|   | 5      |
|   | 6      |
|   | 7      |
|   | 8      |
|   | 10     |
| Short-time protection (std): delay (tsd)                | 100 ms |
| Instantaneous protection (li): dial setting coefficient | 1      |

**Sustainability**

|              |     |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|