



SF263

**2 pole Changeoverswitch 63A I-0-II**

**Technical Features**

**Architecture**

Number of poles	2
Type of pole	2P

**Electric current**

Rated current	63 A
Rated conditional short-circuit current Icc with gl-gG fuses	6 kA

**Installation, mounting**

Nominal tightening torque	2.90 - 2.90 Nm
---------------------------	----------------

**Voltage**

Rated operational voltage Ue	230 - 230 V
Type voltage supply	AC
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4000 V

**Capacity**

Number of modules	4
-------------------	---

**Safety**

Ingress Protection (IP) class	IP20
-------------------------------	------

**Frequency**

Frequency	50 - 60 Hz
-----------	------------

**Dimensions**

Height	90 mm
Width	71.50 mm
Depth	72 mm
Dimensions	90 x 71.50 mm

**Equipment**

Number of NO contacts	0
Number of NC contacts	0

**Use conditions**

Operating temperature	-25 - 50 °C
Storage/transport temperature	-40 - 80 °C

**Connection**

Cross-section flexible conductor	16 mm <sup>2</sup>
Cross-section rigid conductor	25 mm <sup>2</sup>

**Endurance**

Number of mechanical operations	100000
Electrical durability at nominal load in AC21 in operating cycles	5000

**Power**

Total power loss under IN	3.60 W
---------------------------	--------

**Sustainability**

RoHS conform	Yes
--------------	-----

Illustrations | Drawings

