



HEW631NR

**Moulded Case Circuit Breaker h3+ P630 Energy 4P4D N0-50-100% 630A 70kA FTC**

**Technical Features**

**Electric current**

Rated current	630 A
---------------	-------

**Architecture**

Number of poles	4
-----------------	---

Control/operation element	Toggle
---------------------------	--------

Device construction type	Fixed built-in
--------------------------	----------------

Neutral position	Left
------------------	------

**Electric current**

Rated ultimate short-circuit breaking capacity Icu under 400 V AC IEC 60947-2	70 kA
-------------------------------------------------------------------------------	-------

Rated ultimate short-circuit breaking capacity Icu under 240 V AC IEC 60947-2	100 kA
-------------------------------------------------------------------------------	--------

Rated ultimate short-circuit breaking capacity Icu under 415 V AC IEC 60947-2	70 kA
-------------------------------------------------------------------------------	-------

Rated ultimate short-circuit breaking capacity Icu under 690 V AC IEC 60947-2	12 kA
-------------------------------------------------------------------------------	-------

Rated service breaking capacity Ics under 220 V AC according to IEC 60947-2	100 kA
-----------------------------------------------------------------------------	--------

Rated service breaking capacity Ics under 230 V AC according to IEC 60947-2	100 kA
-----------------------------------------------------------------------------	--------

Rated service breaking capacity Ics under 240 V AC according to IEC 60947-2	100 kA
-----------------------------------------------------------------------------	--------

Rated service breaking capacity Ics under 380 V AC according to IEC 60947-2	70 kA
-----------------------------------------------------------------------------	-------

Rated service breaking capacity Ics under 400 V AC according to IEC 60947-2	70 kA
-----------------------------------------------------------------------------	-------

Rated service breaking capacity Ics under 415 V AC according to IEC 60947-2	70 kA
-----------------------------------------------------------------------------	-------

Rated service breaking capacity Ics under 690 V AC according to IEC 60947-2	12 kA
-----------------------------------------------------------------------------	-------

Rated current 10°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current 15°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current 20°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current 25°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current 30°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current at 35°C according to IEC 60947	630 A
----------------------------------------------	-------

Rated current at 40°C according to IEC 60947	630 A
----------------------------------------------	-------

Rated current 45°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current 50°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current 55°C according to IEC 60947	630 A
-------------------------------------------	-------

Rated current at 60°C according to IEC 60947	623 A
----------------------------------------------	-------

Rated current 65°C according to IEC 60947	560 A
-------------------------------------------	-------

Rated current 70°C according to IEC 60947	497 A
-------------------------------------------	-------

**Frequency**

Frequency	50 - 60 Hz
-----------	------------

**Voltage**

Rated impulse withstand voltage Uimp	8000 V
--------------------------------------	--------

Rated insulation voltage Ui	800 V
-----------------------------	-------

Rated operational voltage Ue	220 - 690 V
------------------------------	-------------

**Power**

Total power loss under IN	119 W
---------------------------	-------

**Functions**

Trip unit	ENERGY
-----------	--------

**Safety**

Ingress Protection (IP) class	IP4X
-------------------------------	------

**Installation, mounting**

Nominal tightening torque	18 - 18 Nm
---------------------------	------------

Mounting-/Connection Position	Front
-------------------------------	-------

**Cable**

Cable material	Copper Aluminium
----------------	---------------------

# Product Datasheet

## HEW631NR

---

### Compatibility

Compatible with RDC AOB	Yes
Suitable for DIN Rail	No
Suitable for distribution board	Yes

### Dimensions

Height	260 mm
Width	185 mm
Depth	150 mm

### Settings

Adjustment range short-term delayed short-circuit release	341.25 - 6300.0 A
-----------------------------------------------------------	-------------------

### Electrical protection

Long-time overload protection (ltd): delay (tr)	0.5 s 1.5 s 2.5 s 5 s 7.5 s 9 s 10 s 12 s 14 s 16 s
Short-time protection (std): current (Isd)	1.5 2 2.5 3 3.5 4 4.5 5 5.5 6 6.5 7 7.5 8 8.5 9 9.5 10
Short-time protection (std): delay (tsd)	50 ms 100 ms 200 ms 300 ms 400 ms
Instantaneous protection (li): dial setting coefficient	3 3.5 4 4.5 5 5.5 6 6.5 7 7.5 8 8.5 9 9.5 10 10.5 11

### Sustainability

RoHS conform	Yes
--------------	-----