

HMX225

MCB 2P 50kA C-25A 3M

Technical Features

Architecture	
Type of pole	2P
Curve	С
Voltage	
Rated operational voltage Ue	415 - 415 V
Type voltage supply	AC
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	6000 V
Frequency	
Frequency	50 - 60 Hz
Installation, mounting	
Nominal tightening torque	3.5 - 5.0 Nm
Type of top connection for modular devices	Screw terminal
Type of bottom connection for modular devices	Screw terminal
Electric current	
Rated current	
Rated ultimate short-circuit breaking capacity lcu under 230 V AC IEC 60947-2	50 kA
Rated ultimate short-circuit breaking capacity icu under 400 V AC IEC 60947-2	50 kA
nated diffinate short-circuit breaking capacity icu difider 400 V AC IEC 00541-2	30 KA
Main electrical attributes	
Rated short-circuit breaking capacity Icn AC according to IEC 60898-1	50 kA
Installation, mounting	
Nominal tightening torque down terminal	3.60 - 3.60 Nm
Nominal tightening torque top terminal	3.60 - 3.60 Nm
Power	
Total power loss under IN	2.52 W
Endurance	
Electric endurance in number of cycles	4000
Number of mechanical operations	20000
Connection	
Cross-section of input and output with screws, for massive conductors	1 - 70 mm²
Cross-section of input and output with screws, for flexible conductors	1 - 50 mm²
Cross-section flexible conductor	50 mm ²
Cross-section rigid conductor	70 mm ²
Use conditions	
Degree of pollution according to IEC 60664 / IEC 60947-2	3
Class of energy limitation I ² t	
Air humidity protection Operating temperature	For all climates
Capacity Number of modules	2
Number of modules	3
Connectivity	
Top connection alignment for modular devices	Aligned terminal
Down connection alignment for modular devices	Aligned terminal
Dimensions	
Height	90 mm
Width	53 mm
Depth	70 mm

Sustainability

REACh-SVHC free Yes

Illustrations | Drawings

