Product Datasheet SM101C



Yes



SM101C

Communicant Modular multifunction meter

Technical Features

RoHS conform

Frequency	
Frequency	50 - 60 Hz
Dimensions Height	67 mm
Height Width	73 mm
Depth	50 mm
Берит	30 111111
Safety	
Ingress Protection (IP) class	IP20
Capacity	
Number of modules	4
- Talling of Michael	<u>·</u>
Use conditions	
Operating temperature	-10 - 55 °C
Storage/transport temperature	-20 - 70 °C
Connectivity	
Type of connection	Screw terminal
Type of confidence.	
Connection	
Cross-section flexible conductor	0.5 - 4 mm²
Cross-section rigid conductor	0.5 - 4 mm ²
Power	
Total power loss under IN	5 W
Power consumption VA	5 VA
Equipment	
Type of display	Digital
Measurement	
Frequency measuring range	45 - 65 Hz
Type of measuring instrument	Multimeter
Current measurement range	0 - 9999 A
Installation magnetics	
Installation, mounting Mounting on	DIN rail
Woulding on	Dily Tali
Functions	
Accuracy class	0.005
Power cumply	
Power supply Supply voltage	230 V +10%/-15%
Cuppiy voitage	250 V +1070/*1070
Sustainability	
Halogen free	Yes
REACh-SVHC free	Yes
DallC assisfactors	V/