



14157103

Rocker, lab. field, lens, K.5, al., al. anodised

Technical Features

Architecture

| | |
|---------------------------|---------------|
| Control/operation element | Single rocker |
|---------------------------|---------------|

Materials

| | |
|----------------|-----------|
| Colour | Aluminium |
| RAL code | 9006 |
| Surface finish | Matt |
| Material | Aluminium |
| Treatment | Anodised |

Dimensions

| | |
|--------|-------|
| Height | 55 mm |
| Width | 71 mm |
| Depth | 25 mm |

Connectivity

| | |
|---------------|----------------|
| Mounting type | Clamp mounting |
|---------------|----------------|

Equipment

| | |
|--------------------------------|-----|
| Monitoring window/light outlet | Yes |
|--------------------------------|-----|

Accessories

| | |
|---------------------|-----|
| Has labelling field | Yes |
|---------------------|-----|

Safety

| | |
|-------------------------------|------|
| Ingress Protection (IP) class | IP44 |
| Impact resistance IK | IK05 |

Texts

| | |
|----------------------------------|---|
| Imprint | Without imprint |
| Installation mode | Clamp fastening |
| Labelling | With labelling field |
| Lighting | For lighting and monitoring circuit |
| Push button | Also for KNX applications: push-button, 1-gang, and group push-button, 1-gang |
| Rocker switch/rocker push-button | For rocker push-buttons For change-over/intermediate switch |

Suitable for

K.x