



FWB44

FWB encl.,univers,4rows 192 mod cl.II IP44,plain door,650x1050x161mm,brass term.

Technical Features

| Installation, mounting | |
|-----------------------------|----------------------------|
| Suitable for outdoor usage | No |
| Mounting on | Surface mounting |
| | |
| Electric current | |
| Rated current | 125 A |
| Equipment | |
| Number of rails | 16 |
| Number of rows | 4 |
| Number of section in width | 4 |
| With lock | No |
| Has neutral terminal block | Yes |
| | |
| Capacity | |
| Number of modules | 192 |
| Functions | |
| Has protection main switch | No |
| With conduit inlets | Yes |
| | |
| Dimensions | |
| Height | 650 mm |
| Width | 1050 mm |
| Depth | 165 mm |
| Cover, door | |
| Number of cabinet doors | 2 |
| Name of Samuel access | |
| Dimensions | |
| Built-in depth | 161 mm |
| Cover, door | |
| Number of locks | 0 |
| | |
| Dimensions | |
| Number of width units | 48 |
| Cover, door | |
| Type of handle | Hinged pattern handle |
| Door/cover is transparent | No |
| Dou/Cover is transparent | INO |
| Connection | |
| Number of conduit inlets | 16 |
| Commonthister | |
| Connectivity Mounting type | Curfoco mounting |
| Mounting type | Surface mounting |
| Materials | |
| Material | Steel |
| RAL code | 9010 |
| Colour | Pure white |
| Equipment | |
| Equipment | Voc |
| Has earthing terminal block | Yes |
| Has mounting plate | No |
| 0-1-1 | |
| Safety | |
| Protection class | Isolation class II |
| | Isolation class II IK09 |

Product Datasheet

FWB44



Safety Ingress Protection (IP) class IP44 Locking type Bar lock Without lock Sustainability RoHS conform