



VS108TF1



Small distributor,golf,surface,1row,IP40,8M,MS-terminal,N+PE,transparent door

Technical Features

Tooling at Folder 50	
Voltage	
Nominal voltage	400 - 400 V
Installation, mounting	
Suitable for outdoor usage	No
Mounting on	Surface mounting
Electric current Rated current	63 A
Rated current	
Equipment	
Number of rails	1
Number of rows	1
Number of section in width	1
With lock	No
Has neutral terminal block	No
Capacity	
Number of modules	8
Functions	
With conduit inlets	Yes
With conduit lines	100
Dimensions	
Height	184 mm
Width	210 mm
Depth	99 mm
Cover, door	
Number of cabinet doors	1
Number of locks	0
Dimensions	
Number of width units	8
Cover, door	
Door/cover is transparent	Yes
Materials	
Material	Plastic
RAL code	9010
Colour	Pure white
Equipment	
Has earthing terminal block	Yes
Has mounting plate	No
Materials	
Ultraviolet-resistant	No
- Chiaviolot Toolotant	
Safety	
Protection class	Isolation class II
Impact resistance IK	IK07
Locking type	Snap on lock Without lock
Glow wire test	650 °C
Contain ability	
Sustainability	
REACh-SVHC free	Yes

RoHS conform

Yes