

16511969

Rocker f.accessible const.,tactile symb. .door,redlens,S.1/B.3/B.7,p.wh.m.plas.

Technical Features

| Architecture | |
|----------------------------------|--|
| Control/operation element | Single rocker |
| | |
| Materials Colour | Polar white |
| RAL code | 9010 |
| Surface finish | Matt |
| Material | Thermoplastic |
| Treatment | Untreated |
| neaunent | Ontreated |
| Dimensions | |
| Height | 54.90 mm |
| Width | 55.70 mm |
| Depth | 22 mm |
| | |
| Connectivity | |
| Mounting type | Clamp mounting |
| Equipment | |
| Monitoring window/light outlet | Yes |
| | |
| Accessories | |
| Has labelling field | No |
| Safety | |
| Ingress Protection (IP) class | IP20 |
| Impact resistance IK | IK05 |
| | |
| Texts | |
| Imprint | Without imprint |
| Installation mode | Clamp fastening |
| Push button | Also for KNX applications: push-button, 1-gang |
| Rocker switch/rocker push-button | For illuminated rocker push-buttons |
| | |
| Suitable for | |
| S.x/B.x | |
| • | |
| Sustainability | |
| Halogen free | Yes |
| REACh-SVHC free | Yes |
| RoHS conform | Yes |