

Yes



WGCXEDR500EG

40-500W single dimmer;eg

Technical Features

RoHS conform

| Toolingar Foataroo | |
|-------------------------------------|---------------------------|
| Voltage | |
| Operating voltage | 0-230 V |
| Rated operational voltage Ue | 0-230 V |
| Connectivity | |
| With bus system KNX radio | No |
| Frequency | |
| Frequency | 50-60 Hz |
| Electric current | |
| Control current | 170-2170 mA |
| Materials | |
| Colour | Gold |
| Material | Polycarbonate (PC) |
| Dimensions | |
| Built-in depth | 34 mm |
| Height | 41 mm |
| Width | 86 mm |
| Depth | 41 mm |
| Architecture | |
| Control/operation element | Dimmer |
| Power | |
| 230 V incandescent and halogen lamp | 500 W |
| Power incandescent lamp | 40-500 W |
| Lighting | |
| Dimmable 230 V LED lamp | 40-250 W |
| LED lamp power | 40 W |
| Use conditions | |
| Operating temperature | -5-45 °C |
| Connection | |
| Cross-section rigid conductor | 1.5 - 2.5 mm ² |
| Cross-section flexible conductor | 1.5 - 2.5 mm² |
| Capacity | |
| Number of modules | 1 |
| Sustainability | |