

VF108PT2

Small distributor,golf,flush,1row,8M,IP40,MS-terminal,ANZ,N+PE,white door

Technical Features

| Voltage | |
|--|--------------------|
| Nominal voltage | 400 - 400 V |
| Installation, mounting | |
| Suitable for outdoor usage | No |
| Mounting on | Flush mounting |
| Electric current | |
| Rated current | 80 A |
| Equipment | |
| Number of rails | 1 |
| Number of rows | 1 |
| Number of section in width | 1 |
| With lock | No |
| Has neutral terminal block | Yes |
| Capacity | |
| Number of modules | 8 |
| | |
| Functions | |
| With conduit inlets | Yes |
| Dimensions | |
| Height | 225 mm |
| Width | 275 mm |
| Depth | 97.50 mm |
| Built-in height | 189 mm |
| Built-in width | 242 mm |
| Cover, door | |
| Number of cabinet doors | 1 |
| Dimensions | |
| Built-in depth | 72 mm |
| Cover, door | |
| Number of locks | 0 |
| Dimensions | |
| Number of width units | 8 |
| | |
| Cover, door Door/cover is transparent | No |
| Dool/cover is transparent | INO |
| Materials | |
| Material | Plastic |
| RAL code | 9010 |
| Colour | Pure white |
| Equipment | |
| Has earthing terminal block | Yes |
| Has mounting plate | No |
| Materials | |
| Ultraviolet-resistant | No |
| Safety | |
| Protection class | Isolation class II |
| Impact resistance IK | IK07 |

Product Datasheet

VF108PT

| Safety | |
|----------------|------------------------------|
| Locking type | Snap on lock Without lock |
| Glow wire test | 850 °C |
| Sustainability | |
| RoHS conform | Yes |