

# Product Datasheet

## HHT126BR



HHT126BR

### Moulded Case Circuit Breaker h3+ P250 MAG 4P4D 125A 25kA FTC

#### Technical Features

##### Electric current

Rated current	125 A
Rated ultimate short-circuit breaking capacity Icu under 400 V AC IEC 60947-2	25 kA
Rated ultimate short-circuit breaking capacity Icu under 240 V AC IEC 60947-2	35 kA
Rated service breaking capacity Ics under 230 V AC according to IEC 60947-2	35 kA
Rated service breaking capacity Ics under 400 V AC according to IEC 60947-2	25 kA

##### Architecture

Number of poles	4
Control/operation element	Toggle
Device construction type	Fixed built-in
Neutral position	Left

##### Frequency

Frequency	50 - 60 Hz
-----------	------------

##### Voltage

Rated impulse withstand voltage Uimp	8000 V
Rated insulation voltage Ui	800 V

##### Functions

Trip unit	MAG (ICB)
-----------	-----------

##### Power

Total power loss under IN	27.90 W
---------------------------	---------

##### Endurance

Electric endurance in number of cycles	10000
Number of mechanical operations	40000

##### Safety

Ingress Protection (IP) class	IP4X
-------------------------------	------

##### Connection

Cross-section flexible conductor	35 - 150 mm <sup>2</sup>
Cross-section rigid conductor	35 - 185 mm <sup>2</sup>

##### Installation, mounting

Nominal tightening torque	12 - 12 Nm
Mounting-/Connection Position	Front

##### Cover, door

Interlockable	Yes
---------------	-----

##### Cable

Cable material	Copper Aluminium
----------------	---------------------

##### Dimensions

Height	165 mm
Width	140 mm
Depth	97 mm

##### Compatibility

Compatible with RDC AOB	Yes
Suitable for DIN Rail	No
Suitable for distribution board	Yes

Product Datasheet

HHT126BR

Electrical protection

Instantaneous protection (li): dial setting coefficient	6
	8
	10
	13

Sustainability

REACH-SVHC free	Yes
RoHS conform	Yes