



LFS600600VERZ


## Trunking LFS made of steel 60x60mm galvanized

## **Technical Features**

| Dimensions   |                                |
|--|--------------------------------|
| Height   | 60 mm                          |
| Width  | 60 mm                          |
| Length   | 2000 mm                        |
| Inner cross-section  | 2860 - 2860 mm²                |
| Capacity   |                                |
| Max. number of cables (Ø11mm, 50% filled, without devices) | 12                             |
| Materials  |                                |
| Material   | Steel                          |
| Treatment  | Galvanised                     |
| Colour   | Zinc                           |
| Safety   |                                |
| Impact resistance IK                                       | IK08                           |
| Ingress Protection (IP) class                              | IP30                           |
| Standards  |                                |
| Suitable for functional integrity according to DIN4102-12  | No                             |
| Use conditions   |                                |
| Operating temperature                                      | -5 - 90 °C                     |
| Connectivity   |                                |
| Trunking coupling  | Couplers as separate reference |
| Equipment  |                                |
| Number of partitions                                       | 0                              |
| Number of compartments                                     | 1-1                            |
| Number of pluggable partitions                             | 0                              |
| Cable retaining clip included                              | Yes                            |
| With protective film                                       | No                             |
| Sustainability   |                                |
| Halogen free   | Yes                            |
| REACh-SVHC free  | Yes                            |
| D 110 (  |                                |

## Illustrations | Drawings

RoHS conform



Yes