



Metered 17way 100A MID Pulsed, Modbus

Technical Features

Installation, mounting

| | |
|-------------|------------------|
| Mounting on | Surface mounting |
|-------------|------------------|

Architecture

| | |
|-----------------|---|
| Number of poles | 2 |
|-----------------|---|

Functions

| | |
|----------------------------|-----|
| Has protection main switch | Yes |
|----------------------------|-----|

Capacity

| | |
|-------------------|----|
| Number of modules | 17 |
|-------------------|----|

Electric current

| | |
|---------------|-------|
| Rated current | 100 A |
|---------------|-------|

Dimensions

| | |
|--------|--------|
| Depth | 125 mm |
| Height | 236 mm |
| Width | 505 mm |

Cover, door

| | |
|---------------------------|----|
| Interlockable | No |
| Door/cover is transparent | No |

Materials

| | |
|----------|------------|
| RAL code | 7035 |
| Colour | Light grey |
| Material | Steel |

Connection

| | |
|-----------------------------|---|
| Number of accessible phases | 2 |
|-----------------------------|---|

Scope of delivery

| | |
|-----------------------------|---|
| Number of RCCB in enclosure | 0 |
|-----------------------------|---|

Equipment

| | |
|-------------------|-----|
| Number of rows | 1 |
| With energy meter | Yes |

Safety

| | |
|-------------------------------|-------------------|
| Ingress Protection (IP) class | IP2XC |
| Protection class | Isolation class I |