



NFT732

MCB 1P+N 6/10kA C-32A 1M

Technical Features

Architecture

Type of pole	1P+N
Curve	C

Electric current

Rated current	32 A
Rated service breaking capacity Ics AC according to IEC 60898-1	6 kA
Rated short-circuit breaking capacity Icn under 230 V AC according to IEC 60898-1	6 kA
Min./max. threshold value of the AC thermal operation	1.13 - 1.45 A
Min./max. threshold value of the DC thermal operation	0 - 0 A
Rated current -25°C	38.15 A
Rated current at -20°C	37.63 A
Rated ultimate short-circuit breaking capacity Icu under 230 V AC IEC 60947-2	10 kA
Rated current -15°C	37.11 A
Rated current -10°C	36.58 A
Rated current -5°C	36.04 A
Rated current at 0°C	35.49 A
Rated current 5°C	34.94 A
Rated current 10°C	34.37 A
Rated current 15°C	33.80 A
Rated current at 20°C	33.21 A
Rated current 25°C	32.61 A
Rated current 30°C	32 A
Rated current 35°C	31.57 A
Rated current at 40°C	31.14 A
Rated current at 45°C	30.70 A
Rated current at 50°C	30.25 A
Rated current 55°C	29.80 A
Rated current 60°C	29.34 A
Correction factor of rating current for 2 devices placed side by side	0.95
Correction factor of rating current for 3 devices placed side by side	0.95
Correction factor of rating current for 4 and 5 devices placed side by side	0.90
Correction factor of rating current for 6 devices placed side by side	0.85

Main electrical attributes

Rated short-circuit breaking capacity Icn AC according to IEC 60898-1	6 kA
---	------

Voltage

Rated operational voltage Ue	230 - 240 V
Type voltage supply	AC
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4000 V
Max. operating voltage	253 V

Frequency

Frequency	50 - 60 Hz
-----------	------------

Capacity

Number of modules	1
-------------------	---

Installation, mounting

Type of top connection for modular devices	Screw terminal
Type of bottom connection for modular devices	Screw terminal
Nominal tightening torque	1.90 - 1.90 Nm

Power

Total power loss under I _N	5.50 W
---------------------------------------	--------

Product Datasheet

NFT732

Use conditions	
Operating temperature	-25 - 60 °C
Max. Altitude	2000 m
Endurance	
Electric endurance in number of cycles	4000
Number of mechanical operations	20000
Safety	
Ingress Protection (IP) class	IP20
Grid distance	60 mm
Connectivity	
Type of connection	Screw terminal
Top connection alignment for modular devices	Shifted terminal
Down connection alignment for modular devices	Shifted terminal
Dimensions	
Height	84.70 mm
Width	17.70 mm
Depth	70 mm
Sustainability	
RoHS conform	Yes

Illustrations | Drawings

