Product Datasheet JPE0EXTDW



0



JPE0EXTDW1

Extension Box, elite, 2x28 Modules, grey, 400x600x250mm

To

Number of poles

Connection Number of accessible phases 0 Installation, mounting Mounting Equipment Surface mounting Number of rows 2 With lock Yes Has mounting plate No Capacity Number of modules Number of modules 48 Dimensions 48 Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Cover, door Door/cover is transparent No Materials Steel RAL code 7035 Colour Light grey Safety Select Protection class Isolation class I Impact resistance IK IKO5 Impress Protection (IP) class Isolation class I Imgress Protection (IP) class Isolation class I Imgress Protection (IP) class Isolation class I Impress Protection (IP) class Isolation class I Impress Protection (IP) class <th>Technical Features</th> <th></th>	Technical Features	
Installation, mounting Mounting on Surface mounting Equipment Number of rows 2 With lock Yes Has mounting plate No Capacity Number of modules 48 Dimensions Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Door/cover is transparent No Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock	Connection	
Mounting on Surface mounting Equipment 2 Number of rows 2 With lock Yes Has mounting plate No Capacity Number of modules 48 Dimensions Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Voor/cover is transparent No Materials Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class I mpact resistance IK IKO5 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock	Number of accessible phases	0
Mounting on Surface mounting Equipment 2 Number of rows 2 With lock Yes Has mounting plate No Capacity Number of modules 48 Dimensions Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Voor/cover is transparent No Materials Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class I mpact resistance IK IKO5 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock	Installation, mounting	
Equipment Number of rows 2 With lock Yes Has mounting plate No Capacity Number of modules 48 Dimensions Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Coor/cover is transparent No Materials Steel RAL code 7035 Colour Light grey Safety Protection class I solation class I mpact resistance IK IKO5 Ingress Protection (IP) class Isolation class I ever Key lock		Surface mounting
Number of rows 2 With lock Yes Has mounting plate No Capacity		
With lock Yes Has mounting plate No Capacity 48 Number of modules 48 Dimensions		
Has mounting plate No Capacity Number of modules 48 Dimensions Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Door/cover is transparent No Materials Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock		
Capacity Number of modules 48 Dimensions Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door No Materials No Material Steel RAL code 7035 Colour Light grey Safety Isolation class Impact resistance IK IK05 Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock		
Number of modules48Dimensions400 mmHeight400 mmWidth600 mmDepth250 mmNumber of width units24Cover, doorVolume of width unitsMaterialsNoMaterialSteelRAL code7035ColourLight greySafetyProtection classI solation class I mpact resistance IKIK05Ingress Protection (IP) classIP66Locking type3-point lever Key lock	Has mounting plate	No
Number of modules48Dimensions400 mmHeight400 mmWidth600 mmDepth250 mmNumber of width units24Cover, doorVolume of width unitsMaterialsNoMaterialSteelRAL code7035ColourLight greySafetyProtection classI solation class I mpact resistance IKIK05Ingress Protection (IP) classIP66Locking type3-point lever Key lock	Capacity	
Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Door/cover is transparent No Materials Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock		48
Height 400 mm Width 600 mm Depth 250 mm Number of width units 24 Cover, door Door/cover is transparent No Materials Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock	Dimensions	
Width 600 mm Depth 250 mm Number of width units 24 Cover, door Door/cover is transparent No Materials Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock		400 mm
Depth 250 mm Number of width units 24 Cover, door Door/cover is transparent No Materials Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock		
Number of width units 24 Cover, door Door/cover is transparent No Materials Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock		
Door/cover is transparentNoMaterialsSteelRAL code7035ColourLight greySafetyProtection classIsolation class IImpact resistance IKIK05Ingress Protection (IP) classIP66Locking type3-point lever Key lock	<u> </u>	
Door/cover is transparentNoMaterialsSteelRAL code7035ColourLight greySafetyProtection classIsolation class IImpact resistance IKIK05Ingress Protection (IP) classIP66Locking type3-point lever Key lock		
MaterialsMaterialSteelRAL code7035ColourLight greySafetyProtection classIsolation class IImpact resistance IKIK05Ingress Protection (IP) classIP66Locking type3-point lever Key lock		
Material Steel RAL code 7035 Colour Light grey Safety Protection class Isolation class I Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock	Door/cover is transparent	No
RAL code 7035 Colour Light grey Safety Protection class Isolation class I Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock	Materials	
ColourLight greySafetyProtection classIsolation class IImpact resistance IKIK05Ingress Protection (IP) classIP66Locking type3-point lever Key lock	Material	Steel
Safety Protection class Impact resistance IK IK05 Ingress Protection (IP) class IP66 Locking type 3-point lever Key lock	RAL code	7035
Protection class I Isolation class I Impact resistance IK IK05 Ingress Protection (IP) class I IP66 Locking type 3-point lever Key lock	Colour	Light grey
Protection class I Isolation class I Impact resistance IK IK05 Ingress Protection (IP) class I IP66 Locking type 3-point lever Key lock	Safety	
Ingress Protection (IP) class Locking type 3-point lever Key lock		Isolation class I
Ingress Protection (IP) class Locking type 3-point lever Key lock	Impact resistance IK	
Locking type 3-point lever Key lock		IP66
Key lock		3-point lever
Architecture		
	Architecture	