



ECM140D

### 1 Phase kWhmeter direct 40A 1M MBUS MID

#### Technical Features

##### Architecture

Bus system	M-BUS
Type of pole	1P+N

##### Electric current

Rated current	40 A
---------------	------

##### Capacity

Number of modules	1
-------------------	---

##### Connectivity

Type of connection	Direct connection
--------------------	-------------------

##### Dimensions

Height	92 mm
Width	18 mm
Depth	60 mm

##### Equipment

Type of pulse generator	Optical
-------------------------	---------

##### Compatibility

Suitable for	Purchase/supply
--------------	-----------------

##### Connection

Cross-section of metering input	16 - 16 mm <sup>2</sup>
Cross-section of metering output	16 - 16 mm <sup>2</sup>
Connector/plug type Bus system	Bus connection terminal

##### Installation, mounting

Nominal tightening torque	1 - 1 Nm
Mounting on	DIN rail

##### Mechanical features

Nominal tightening torque digital terminal	0.50 - 0.50 Nm
--	----------------

##### Measurement

Measuring system	Direct measurement
Type of measuring instrument	Electronic
Current measurement range	0.25 - 40.0 A
Measurement range voltage Ph-N	92 - 276 V
Frequency measuring range	45 - 65 Hz

##### Power supply

Number of phases for power supply	1
-----------------------------------	---

##### Functions

Accuracy class	B
Tariff type	- /T1...T2 M-BUS
Is calibrated	Yes

##### Safety

Ingress Protection (IP) class	IP20
-------------------------------	------

##### Use conditions

Operating temperature	-25 - 55 °C
Storage/transport temperature	-25 - 70 °C

##### Power

Power consumption VA	2 VA
Total power loss under IN	1 W

# Product Datasheet

## ECM140D

---

<b>Electric current</b>	
Maximum measuring circuit current	40 A
<b>Frequency</b>	
Frequency	50 - 50 Hz
<b>Sustainability</b>	
REACH-SVHC free	Yes
RoHS conform	Yes