Product Datasheet LR701





I R701

Fuse carrier 1P 125A 690V L58 2M

Technical Features

Dimensions	105
Height	125 mm
Width Depth	35 mm 96 mm
Бери і	30 111111
Architecture	
Number of poles	1
Electric current	
Rated current	125 A
Rated current of fuse cartridge	16 A 20 A 25 A 32 A 40 A 50 A 80 A
	100 A 125 A
Capacity	
Number of modules	2
Line conditions	
Use conditions Operating temperature	-5 - 40 °C
Operating temperature	0 40 0
Installation, mounting	
Nominal tightening torque	4 - 4 Nm
Mounting on	DIN rail
Power	
Total power loss under IN	12.84 W
W.H.	
Voltage Rated insulation voltage Ui	600 V
Rated impulse withstand voltage Uimp	690 V 8 kV
Type voltage supply	AC
Overvoltage category according to IEC 60947-1	3
Safety	
Ingress Protection (IP) class	IP20
Connection	
Cross-section of input and output with screws, for flexible conductors	2.55 - 35 mm²
Cross-section of input and output with screws, for massive conductors	2.5 - 50 mm ²
	2.0 00 11111
Fuse size	22 x 58
ruse size	22 X 30
Cover, door	
Interlockable	No
Sustainability	
REACh-SVHC free	Yes
	Yes