



SPL212R

SPD 2P T1+T2 TNS/TT Uc 350V Iimp 12.5kA remote contact

Technical Features

Network configuration

Network type	TN-S TT
--------------	------------

Electric current

Max. overcurrent protection device, parallel connection (fuse)	160 A
--	-------

Connectivity

Type of connection	Screw terminal
--------------------	----------------

Electric current

Lightning impulse current Iimp (10/350 μs) IEC 61643 L-N(PEN)/ N-PE	12.5 kA 50 kA
---	------------------

Equipment

With remote signalling contact	Yes
--------------------------------	-----

Capacity

Number of modules	2
-------------------	---

Voltage

Voltage protection level Up according to IEC 61643-1	1.50 kV
Continuous operating voltage Uc according to IEC 61643-1	350 V
Rated operational voltage Ue	230 - 400 V
Voltage level Up L-N/PEN IEC 61643-11	1.5 kV

Architecture

Number of poles	2
-----------------	---

Use conditions

Operating temperature	-40 - 85 °C
-----------------------	-------------

Dimensions

Height	67.6 mm
Width	36 mm
Depth	90 mm

Controls and indicators

With indicator lamp	Yes
---------------------	-----

Standards

Requirement class IEC 61643	T1
-----------------------------	----

Installation, mounting

Nominal tightening torque	2.50 - 2.50 Nm
---------------------------	----------------

Connection

Cross-section of input and output with screws, for flexible conductors	25 - 25 mm ²
Cross-section of input and output with screws, for massive conductors	35 - 35 mm ²
Cross-section signal contact	0.1 - 1.5 mm ²

Frequency

Frequency	50 - 60 Hz
-----------	------------

Safety

Ingress Protection (IP) class	IP20
-------------------------------	------

Sustainability

RECh-SVHC free	Yes
RoHS conform	Yes