Product Datasheet LR601



Yes



1 0004

Fuse carrier 1P 50A 690V L51 1.5M

Technical Features

Dimensions Light	107 mm
Height Width	26.25 mm
Depth	20.25 Milli
—	95 11111
Architecture	
Number of poles	1
Electric current	
Rated current	50 A
Rated current of fuse cartridge	2 A
	4 A
	6 A 8 A
	10 A
	12 A
	16 A
	20 A 25 A
	32 A
	40 A
	50 A
Capacity	
Number of modules	1.50
Use conditions	
Operating temperature	-5 - 40 °C
Installation, mounting	
Nominal tightening torque	3.5 - 3.5 Nm
Mounting on	DIN rail
Power	
Total power loss under IN	6 W
Voltage	
Rated insulation voltage Ui	690 V
Rated impulse withstand voltage Uimp	8 kV
Type voltage supply	AC
Overvoltage category according to IEC 60947-1	3
Safety	
Ingress Protection (IP) class	IP20
Connection	
Cross-section of input and output with screws, for flexible conductors	2.5 - 25 mm²
Cross-section of input and output with screws, for massive conductors	2.5 - 35 mm²
Fuse	
Fuse size	14 x 51
Cover, door	K.1 -
Interlockable	No
Sustainability	
REACh-SVHC free	Yes

RoHS conform