

Yes



WFSS82PSB-USBSAC

## DP Switched Socket 13A 2G USB A+C ports Polished Steel Black Flat

## **Technical Features**

recillical reactives	
Electric current	
Rated current	13 A
Voltage	
Nominal voltage	230 - 230 V
Fraguency	
Frequency Frequency	50 - 50 Hz
rrequericy	30 - 30 112
Materials	
Surface finish	Glossy
Material	Stainless steel
Dimensions	
Height	86 mm
Width	146 mm
Depth	16 mm
Built-in depth flush-mounted boxes	25 mm
Installation, mounting	
Mounting on	Flush mounting
Mounting-/Connection Position	Horizontal
Connectivity	
Type of connection	Screw terminal
Mounting type	Screw mounting
Connector/plug type USB	AC
Equipment	
Connector/plug type socket outlet	British Standard
Rotated central insert	No
With hinged lid	No
With round protective earth pin	No
With signal lamp	No
Accessories	
Has labelling field	No
Capacity	
Number of modules	0
Safety Ingress Protection (IP) class	IP20
Ingress Flutection (IF) class	IFZU
Functions	
With orientation lighting	No
With function lighting	No
Texts	
Imprint	With imprint
Cover	Full cover plate
Wiring	With double earth connection
Protection	Enhanced contact protection
Sustainability	
REACh-SVHC free	Yes

RoHS conform