



K7T1M1W

10A Luminaire Lead 1m 1mm 6 Core Plug to Wire

Technical Features

Architecture

| | |
|-----------------|---|
| Number of poles | 6 |
|-----------------|---|

Voltage

| | |
|------------------------|-------|
| Max. operating voltage | 240 V |
|------------------------|-------|

Electric current

| | |
|---------------|------|
| Rated current | 10 A |
|---------------|------|

Cable

| | |
|----------------|-------|
| Cable diameter | 10 mm |
|----------------|-------|

Connection

| | |
|-------------------------|-----------------------|
| Conductor cross-section | 1 - 1 mm ² |
|-------------------------|-----------------------|

Equipment

| | |
|-------------------|-----|
| Mechanical coding | Yes |
|-------------------|-----|

| | |
|-------------------|------|
| Type cable side 1 | Plug |
|-------------------|------|

| | |
|-------------------|--------------------|
| Type cable side 2 | Free conductor end |
|-------------------|--------------------|

| | |
|---------------|-------------------------|
| Type of cable | Device connection cable |
|---------------|-------------------------|

Use conditions

| | |
|--|---|
| Degree of pollution according to IEC 60664 / IEC 60947-2 | 2 |
|--|---|

Materials

| | |
|--------|-------|
| Colour | White |
|--------|-------|

Cable

| | |
|--|-------|
| Cable permanent temperature resistant to | 90 °C |
|--|-------|

Sustainability

| | |
|-----------------|-----|
| REACH-SVHC free | Yes |
|-----------------|-----|

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|