



NGN201

# MCB 2P 6/10kA D-1A 2M

#### **Technical Features**

Electric current	
Rated current	1 A
Rated service breaking capacity lcs under 230 V AC according to IEC 60947-2	15 kA
Rated short-circuit breaking capacity Icn under 230 V AC according to IEC 60898-1	10 kA
Rated ultimate short-circuit breaking capacity Icu under 230 V AC IEC 60947-2	20 kA
Rated ultimate short-circuit breaking capacity Icu under 400 V AC IEC 60947-2	10 kA
3 11/11/20	
Architecture	
Type of pole	2P
Curve	D
Capacity	
Number of modules	2
Main electrical attributes	
Rated short-circuit breaking capacity Icn AC according to IEC 60898-1	6 kA
Installation, mounting	
Nominal tightening torque top terminal	2.80 - 2.80 Nm
Nominal tightening torque down terminal	2.80 - 2.80 Nm
Terrinal agricing torque dewn terrinal	2.00 2.00 WIII
Voltage	
Rated operational voltage Ue	400 - 400 V
Type voltage supply	AC
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	6000 V
Frequency	
Frequency	50 - 60 Hz
Connection	
Cross-section of input and output with screws, for massive conductors	1 - 35 mm²
Cross-section of input and output with screws, for flexible conductors	1 - 25 mm <sup>2</sup>
Cross-section of input with screws, for flexible conductors	1 - 25 mm <sup>2</sup>
Cross-section of input with screws, for massive conductors	1 - 35 mm <sup>2</sup>
Cross-section of input with sciews, for massive conductors	1 - 33 111111
Installation, mounting	
Nominal tightening torque	2.80 - 2.80 Nm
Type of bottom connection for modular devices	biconnect
Type of top connection for modular devices	Screw terminal
360° mounting position possible	Yes
Safety	
Ingress Protection (IP) class	IP20
Grid distance	60 mm
Use conditions	
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Operating temperature	-25 - 70 °C
-	
Power Total power loss under IN	2.11 W
	Z.11 VV
Connectivity	
Type of connection	Screw terminal
Top connection alignment for modular devices	Aligned terminal

Top connection alignment for modular devices

Down connection alignment for modular devices

Aligned terminal



### Dimensions

Height	83 mm
Width	35 mm
Depth	70 mm

# Sustainability

RoHS conform	Yes
--------------	-----

# Illustrations | Drawings



