



LSN501

### Fuse carrier 1P 32A 690V L38 1M

#### Technical Features

##### Dimensions

Height	76.50 mm
Width	17.50 mm
Depth	76.90 mm

##### Architecture

Number of poles	1
-----------------	---

##### Electric current

Rated current	32 A
Rated current of fuse cartridge	0.2 A 1 A 2 A 4 A 6 A 8 A 10 A 12 A 16 A 20 A 25 A 32 A

##### Capacity

Number of modules	1
-------------------	---

##### Use conditions

Operating temperature	-40 - 70 °C
-----------------------	-------------

##### Installation, mounting

Nominal tightening torque	2.20 - 2.20 Nm
Mounting on	DIN rail

##### Power

Total power loss under IN	3.40 W
---------------------------	--------

##### Voltage

Rated insulation voltage $U_i$	1000 V
Rated impulse withstand voltage $U_{imp}$	6000 V
Type voltage supply	AC/DC
Overvoltage category according to IEC 60947-1	3

##### Safety

Ingress Protection (IP) class	IP2X
-------------------------------	------

##### Connection

Cross-section of input and output with screws, for flexible conductors	1 - 16 mm <sup>2</sup>
Cross-section of input and output with screws, for massive conductors	1 - 16 mm <sup>2</sup>

##### Fuse

Fuse size	10 x 38
-----------	---------

##### Cover, door

Interlockable	Yes
---------------	-----

##### Sustainability

REACH-SVHC free	Yes
RoHS conform	Yes